



WHEEL CHOCK

PRODUCT SPECIFICATIONS



1910.111(f)(9)

Chock blocks. At least two chock blocks shall be provided. These blocks shall be placed to prevent rolling of the vehicle whenever it is parked during loading and unloading operations.



15300



15301



15337



15341



Model	Material	Tire Size (Diameter)	Dimensions	Weight
15300	Rubber	27 in to 32 in (685 mm to 812 mm)	10 in (L) x 8 in (W) x 6 in (H) 254 mm (L) x 203 mm (W) x 152 mm (H)	8.5 lbs (3.9 kg)
15301	Rubber	47 in to 86 in (1200 mm to 2200 mm)	11 in (L) x 11 in (W) x 10 in (H) 290 mm (L) x 290 mm (W) x 250 mm (H)	22 lbs (10 kg)
15336	Urethane	35 in to 55 in (900 mm to 140 mm)	13.3 in (L) x 8.6 in (W) x 7.8 in (H) 340 mm (L) x 220 mm (W) x 200 mm (H)	7.7 lbs (3.5 kg)
15353	Urethane	47 in to 70 in (1200 mm to 1800 mm)	13.38 in (L) x 9.84 in (W) x 7.8 in (H) 340 mm (L) x 250 mm (W) x 225 mm (H)	13.66 lbs (6.2 kg)
15337	Urethane	47 in to 86 in (1200 mm to 2200 mm)	18 in (L) x 12 in (W) x 9 in (H) 475 mm (L) x 305 mm (W) x 225 mm (H)	13 lbs (6 kg)
15341	Urethane	31 in to 110 in (790 mm to 2790 mm)	22 in (L) x 13 in (W) x 11 in (H) 559 mm (L) x 340 mm (W) x 280 mm (H)	17 lbs (8 kg)
15338	Urethane	70 in to 118 in (1800 mm to 3000 mm)	22.5 in (L) x 13 in (W) x 14 in (H) 570 mm (L) x 340 mm (W) x 355 mm (H)	19.8 lbs (9 kg)
15342	Urethane	86.6 in to 137.8 in (2200 mm to 3500 mm)	24 in (L) x 13.5 in (W) x 12 in (H) 621 mm (L) x 343 mm (W) x 323 mm (H)	24.3 lbs (11 kg)
15339	Urethane	110 in x 165 in (2800 mm to 4200 mm)	26.7 in (L) x 13 in (W) x 14 in (H) 680 mm (L) x 337 mm (W) x 355 mm (H)	30.86 lbs (14 kg)