

ASSOCIATED

MODEL IBC6008MSK

**12V, 60/70A Intelligent Wheel Charger /
Reflash Power Supply, Safe for all
Battery Types SLA, AGM, EFB, Gel,
Lithium-Ion**

IBC6008MSK

- 60A Adjustable Charging Voltage and Amperage
- 70A Adjustable Voltage Re-flash Power Supply
- Partial Charge Mode and Patented Battery Diagnostics
- Designed to Vehicle Manufacturer and Battery Manufacturer Requirements
- Polarity Indicated and Polarity Protected with Audible Messaging
- Memory Saver Port and 12' Cable for Memory Saving
- 2 Year Bumper to Bumper Warranty and 3-Year Coverage on the Transformer and Rectifier

12' Memory Saver Cable



Four-line backlit digital display with 3 languages: English, Spanish, and French



Memory Saver Port

270 Amp Boost

Safe in any weather

500A Vinyl Coat w/Copper Jaws



MADE IN USA OF U.S. AND IMPORTED PARTS
WARNING
 CAUTION: See instruction manual and label panel for proper use and warnings.
 DANGER: Risk of personal injury and property damage if used incorrectly.
 Attention: Read instructions on the use and operation.

ASSOCIATED
 INTELLAMATIC®
SMART CHARGER/ANALYZER
 ADJUSTABLE REFLASH POWER MODE
12 VOLT 60 AMP
270 AMP
 12 VOLT ENGINE START
 AUTOMATIC BATTERY CHARGING & RECONDITIONING
 CHARGE RESIST MAXIMUM ON 8 HRS.
 CONTINUOUS DUTY CHARGE RATING INPUT: 120V AC, 12.8 AMP, 60HZ OUTPUT: 12V DC, 60 AMP DUTY CYCLE: 5 SECONDS ON - 4 MINUTES OFF

MODEL IBC6008MSK
 Patent No. 5,588,913

SAFE FOR AGM VEHICLE BATTERIES



MODEL IBC6008

- *12V 60 Amp 270 Amp Boost wheel charger*
- *Adjustable Charging Voltage and Amperage*
- *Adjustable Voltage Re-flash Power Mode*
- *Partial Charge Mode*
- *Patented Battery Diagnostics*
- *Designed to Vehicle Manufacturer and Battery Manufacturer Requirements*

Specifications:

Model Number	IBC6008
Battery Types	12 Volt Standard Flooded, AGM, Gel, EFB, Lithium and Deep Cycle batteries
Display	Four-line backlit digital display
DC Leads	6 ½' 4 AWG
Clamp Rating	400A
AC Cord	6' 16-3
Power Requirements and Consumption	12A 120VAC 60 Hz
Charger Output	13.8V-60A. Crank 7.2V-260A
Power Supply Output	13.8V – 60A. Can output 70A at lower voltage for <10 min.
Industry Approval	UL/CUL
Limited Warranty	Two Years Parts/Labor-Three Years Transformer/Rectifier
Country of Origin	MADE IN USA of US and Global Components
UPC	099684006972
HTC	8203.10.9000
Shipping Dimensions	17.25"x16.5"x26.5"
Weight	47 LBS



MODEL IBC6008MSK

- *12V 60 Amp 270 Amp Boost wheel charger*
- *Adjustable Charging Voltage and Amperage*
- *Adjustable Voltage Re-flash Power Mode*
- *Partial Charge Mode and Patented Battery Diagnostics*
- *Designed to Vehicle Manufacturer and Battery Manufacturer Requirements*
- *20A Memory Saver Port and OBDII Cable*
- *Polarity Indicated and Polarity Protected with Audible Alarm*

Specifications:

Model Number	IBC6008MSK
Battery Types	12 Volt Standard Flooded, AGM, Gel, EFB, Lithium and Deep Cycle batteries
Display	Four-line backlit digital display
DC Leads	6 ½' 4 AWG
Clamp Rating	400A
AC Cord	6' 16-3
Power Requirements and Consumption	12A 120VAC 60 Hz
Charger Output	13.8V-60A. Crank 7.2V-260A
Power Supply Output	13.8V – 60A. Can output 70A at lower voltage for <10 min.
Memory Saver Port	20A
Memory Saver Cord	MS6209-12 OBDII
Industry Approval	UL/CUL
Limited Warranty	Two Years Parts/Labor-Three Years Transformer/Rectifier
Country of Origin	MADE IN USA of US and Global Components
UPC	099684006989
HTC	8203.10.9000
Shipping Dimensions	17.25"x16.5"x26.5"
Weight	49 LBS