
SPECIFICATION SHEET



MODELS 504 & 505 VERTICAL DISCHARGE FANS



Efficient, high-performance for ceiling installations. Offered in two sizes to meet various room requirements.

FEATURES

GRILLE:

- Contemporary styling for modern homes
- White polymeric grilles can be painted to match any decor

• Aluminum filter available - purchase separately MOTOR:

- Permanently lubricated, thermally protected, plug-in motor
- Specially designed fiberglass-reinforced fan blades
- Motor assembly offers fast, easy "twist-lock" installation HOUSING:
- Galvanized steel housing, 25 gage
- Model 505 (8" model) has built-in backdraft damper
- Adjustable mounting brackets with keyhole slots span 14" to 24"
- Model 472 Reducer-Damper available separately allows Model 504 to use 8" round duct and adds a damper

SPECIFICATIONS

MODEL	VOLTS	AMPS	RPM	SONES	CFM	DUCT
504	120	1.7	1630	8.0	330	10" Rd.
505	120	1.5	2270	8.5	200	8" Rd.



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in.static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

TYPICAL SPECIFICATION

Ventilator shall be Broan Model 504 (Model 505).

Ventilator shall duct vertically, to an outside roof cap. Can be controlled with toggle switch (speed control).

Ventilator shall have galvanized steel housing.

Motor assembly shall be removable and permanently lubricated. RPM shall not exceed 1630 (Model 504), (2270 RPM – Model 505).

Air delivery shall be no less than 330 CFM and sound levels no greater than 8.0 Sones (Model 504) (200 CFM and 8.5 Sones – Model 505). All air and sound ratings shall be certified by HVI. Model 504 shall be U.L. Listed and Model 505 cULus Listed.

