

SIZE

24 in.

BISQUE

## **Under-Cabinet**

NON-DUCTED

FILTERS

HPF24 (Type "Xb")

GI ACIER

"Xc") "Xd") "Xe")







| 30 in.                           | BCSD130BC | BCSD130BL         | BCSD130SS       | BCSD13 | WWO  | HPFA130 (T | ype "C1")            | HPF30 (Type "X          |  |
|----------------------------------|-----------|-------------------|-----------------|--------|------|------------|----------------------|-------------------------|--|
| 36 in.                           | BCSD136BC | BCSD136BL         | BCSD136SS       | BCSD13 | 6WW  | HPFA136 (T | ype "D1")            | HPF36 (Type "X          |  |
| 42 in.                           |           | BCSD142BL         | BCSD142SS       | BCSD14 | 2WW  | HPFA142 (1 | ype "E1")            | HPF42 (Type "X          |  |
| HVI PE                           | RFORMANCE |                   |                 |        |      |            |                      |                         |  |
|                                  |           |                   | Damper          | Sones  |      |            | CFM                  |                         |  |
| Duct Orientation                 |           | Size              |                 | Normal | High | Normal     | High<br>0.25 in. w.g | High<br>g. 0.1 in. w.g. |  |
| Vertical - Rectangular           |           | 3¼ in. x 10 in.   | Included        | 1.5    | 5.0  | 130        | 130                  | 220                     |  |
| Horizontal - Rectangular         |           | r 3¼ in. x 10 in. | Included        | 1.5    | 5.0  | 110        | 128                  | 210                     |  |
| Round - Vertical                 |           | 7 in.             | Sold Separately | 1.5    | 5.0  | 150        | 110                  | 240                     |  |
| FEATURES<br>Max. Blower CEM* 300 |           |                   |                 |        |      |            | 11                   |                         |  |
| Control type 2-speed Rocker      |           |                   | 1               |        |      | 4          |                      |                         |  |

The clean, contemporary shape of Glacier complements any kitchen design. This new design has features like the

WHITE

BCSD124WW

**STAINLESS** 

BCSD124SS

| Max. Blower CFM*                       | 300  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|
| Control type                           | 2-speed Rocker   |  |  |  |  |  |  |  |
| Delay off                              | no   |  |  |  |  |  |  |  |
| Filter Clean Reminder                  | no   |  |  |  |  |  |  |  |
| Heat Sentry™                           | no   |  |  |  |  |  |  |  |
| ADA Capable                            | yes  |  |  |  |  |  |  |  |
| Lighting                               | 2-level 50 W Halogen (not included)                      |  |  |  |  |  |  |  |
| Grease Filters                         | Open Mesh (Qty. 2)                                       |  |  |  |  |  |  |  |
| Installation Hardware                  | EZ1 brackets   |  |  |  |  |  |  |  |
| ENERGY STAR®                           | no   |  |  |  |  |  |  |  |
| Recirculation                          | Non-ducted filters sold separately                       |  |  |  |  |  |  |  |
| AC INPUT                               |  |  |  |  |  |  |  |  |
| 120 V, 60 Hz - 1.4 AMPS                |  |  |  |  |  |  |  |  |
| OPTIONAL ACCESS                        | ORIES  |  |  |  |  |  |  |  |
| 7-in. Round Damper                     | BP87Q  |  |  |  |  |  |  |  |
| Make-up Air Dampers                    | MD6TU, MD8TU and MD10TU                                  |  |  |  |  |  |  |  |
| MOUNTING HEIGHT                        | MOUNTING HEIGHT  |  |  |  |  |  |  |  |
| 18 in. to 24 in. from co               | poktop to bottom of hood                                 |  |  |  |  |  |  |  |
| LIMITED WARRANTY                       |  |  |  |  |  |  |  |  |
| 1-year (See installation               | 1-year (See installation manual for full warranty text.) |  |  |  |  |  |  |  |
| FOR INDOOR USE ONLY                    |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |
| 0.5                                    |  |  |  |  |  |  |  |  |
| (ii) 0.4                               | Vertical High Speed,                                     |  |  |  |  |  |  |  |
| GP 0.4   U   U   0.3   0.2   0.2   0.1 | with 3¼ in. x 10 in. damper                              |  |  |  |  |  |  |  |
| UN 0.2                                 | Horizontal High Speed,<br>with 3½ in. x 10 in. damper    |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |
| ਲੋਂ 0.1                                |  |  |  |  |  |  |  |  |

quiet Captur<sup>™</sup> system and brilliant halogen lighting.

BLACK


BCSD124BL



**GREASE FILTERS** 

(replacement)

HPFA124 (Type "B1")



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanlyperceived loudness, based on laboratory measurements

400

\* Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

250

300

350

0

50

100

150

200

Airflow (cfm)