

0.1 0 0

50

100

Under-Cabinet

NON-DUCTED

SAHAI F

The slim and refined lines of Sahale bring a refreshing change to today's kitchens. Bright ENERGY STAR® certified LED lighting complements your cooking experience and three fan speeds make cooking more enjoyable. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bulbs.

GREASE FILTERS







| SIZE BLA | CK | STAINLES | s whi | WHITE GREASE FIL (replaceme | | | | | | |
|---|-----------|--|--|--------------------------------|----------------------|--------|-------------------|--------------|--|----------------------|
| 30 in. BKDEG130BL BKDEG1 | | L BKDEG130 | 30SS BKDEG130WW | | HPFA3A30 (Type "C3") | | HPF30 (Type "Xc") | | | |
| HVI PERFORMA | NCE | | | | | | | | | |
| | | | | Sones | | CFM | | | | |
| Duct Orientatio | on | Size | Damper | Normal | Medium* | High | Normal | Medium* | High 0.25 in. w.g. | High 0.1 in. w.g. |
| Vertical - Rectangul | | 3¼ in. x 10 in. | Included | 1.5 | 3.0 | 6.0 | 120 | 160 | 140 | 230 |
| Horizontal - Rectan | <u> </u> | 3¼ in. x 10 in. | Included | 1.5 | 3.0 | 6.5 | 110 | 160 | 150 | 230 |
| Round - Vertical | | 7 in. | Sold Separately | 1.5 | 3.0 | 5.5 | 130 | 180 | 115 | 260 |
| FEATURES | | | | | | | | | | |
| Max. Blower CFM | /** | 375 | | | 1/2 | | | | | |
| Control type | | 3-speed Capac | itive Touch | | | | 11 | | | |
| Delay off | | no | | | | | | | | |
| Filter Clean Remi | nder | yes | | | | | | | | |
| Heat Sentry™ | | no | | | a comp | | THEFT | 17527750 | (7.7.7.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1 | |
| ADA Capable | | yes | | | | | 387 | | | |
| Lighting | | 2-level ENERGY STAR [®] LED (included) | | | | | | | | |
| Grease Filters | | Deluxe Micro N | lesh (Qty. 2) | | K & X | | | | | |
| Installation Hardw | vare | EZ1 brackets | | K & X | | | | | | |
| ENERGY STAR® | | ves (no if instal | led non-ducted) | K B | 232 | | | | | |
| Recirculation | | | ers sold separat | | 1× | | | <u>KRAK</u> | 2 | |
| AC INPUT | | | | - / | | | Sauge - | | - | Den 18 |
| 120 V, 60 Hz - 0 |) 65 A | MPS | | | 1. 1. 14 | N P IS | 100 | * * | | |
| OPTIONAL ACC | | | | | | | | | - | |
| 7-in. Round Dam | | BP87Q | | | | | | | | |
| ADA Wiring Kit | · · · · · | HAWRK3 | | | | | | | | |
| Make-up Air Dam | | | Barriskin. | | | | | | | |
| | | | | | | | | | | |
| MOUNTING HE | | oldon to hotto | ofbood | | | | | | | |
| 18 in. to 24 in. fr | | oktop to bottom | | | | | | | | |
| | ANTY | | | | | | | | | |
| 1-year 3-year (LED mod | ابنامه د | | | | | | | | | |
| (See installation r | | | ty text.) | | | ē. | | | \gtrsim \diamond | ير . |
| FOR INDOOR U | | | | | | 52) | ````/// | \sim . | 12 00 × 10 | \sum |
| 0.6 | | | 1 I I | | | | <i>[[]</i> > , | × | \sim | $\sum_{i=1}^{n}$ |
| 0.5 | | | Vertical High Speed 7-in. round | , | | | \checkmark | E 🖉 | > 32 | 5 |
| (→ → → 0.4 | | | Vertical High Speed | | | | \sim | \mathbf{X} | 8 | |
| ein | | | with 3¼ in. x 10 in. | | | \sim | 100 × | | | - |
| D.3 | | | Horizontal High Spe with 3¼ in. x 10 in. | | | Ì | | 5 | Dir | nensions |
| 0.4 0.3 0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.4 | _ | | | | | | | 29 J | | n in inches |
| ⁵⁷ 0.1 | | | | | Ξ. | 97 | - A | ~~~~ | - | |
| 0 | | | | | | 0 | | | | \frown |



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

400

350

* Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure ** Max. blower CFM indicates the performance of the hood blower in open air.

300

250

150

200

Airflow (cfm)



| Broan LED Modules are specially designed for cooking environments | | | | | | | | | |
|---|--------------|--|--|--|--|--|--|--|--|
| | | | | | | | | | |
| Part Number S97020187 (pair) | | | | | | | | | |
| Color Temperature | 3000 K | | | | | | | | |
| Lumens | 450 / module | | | | | | | | |
| Lux at cooktop | 900 | | | | | | | | |
| CRI | 80 | | | | | | | | |
| Ambient temperature rating | 80° C | | | | | | | | |
| Watts | 4.5 / module | | | | | | | | |
| Service life | 25,000 hours | | | | | | | | |
| Warranty | 3 years | | | | | | | | |