

Under-Cabinet

Choose the BUEZ3, 4-way convertible hood for round and rectangular ducted, as well as non-ducted configurations.



	40 TO CO.
-	2019 TITLE CA
Ś	24 H
	Range Hood Requirements


TIFIED

SIZE WHITE ON WHITE		ITE BLAC	K STAINLESS STEEL		GREASE FILTER WITH LIGHT LENS (replacement)		WITH LIC NON-DUC	GREASE FILTER WITH LIGHT LENS & NON-DUCT FILTER PAD (replacement)	
30-in.	BUEZ330WV	V BUEZ33	OBL BUEZ330	SS	R61	10045	R6	10050	
HVI PERFORMANCE									
Duct Orientation					Sones		CFM		
		Size	Damper	Normal	l High	Normal	High 0.25 in. w.g.	High 0.1 in. w.g.	
Vertica	al - Rectangular	3¼-in. x 10-in.	Included	2.0	6.0	100	105	190	
Horizont	tal - Rectangular	3¼-in. x 10-in.	Included	2.0†	7.0	90†	105	160	
Vert	tical - Round	7-in.	BP87Q (purchase separately)	2.0	6.0	130	100	240	


FEATURES						
Max. Blower Airflow	260 CFM†					
Control type	2-speed Rocker					
Lighting	1-level Rocker 1- 75W, A19 incandescent bulb (purchase separately)					
Fan Blade	Polymeric					
Grease Filter with Light Lens	Washable aluminum 11-1/2" x 11-3/4"					
Grease Filter withNon- Duct Filter & Light Lens	R610050 - 11-1/2" x 11-3/4" (purchase separately)					
Installation Hardware	EZ1 brackets					
ADA Compatible	yes					
AC INPUT						
115V, 60 Hz - 1.8 AMPS						
OPTIONAL ACCESSORIES						
ADA Wiring Kit	HAWRK3					
MOUNTING HEIGHT						
18-in. to 24-in. from cooktop to bottom of hood						
LIMITED WARRANTY						

1-year

FOR INDOOR USE ONLY







HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

+ Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.