




WALL CONTROLS




Model CD60W (White)
20-40-60 Minute Countdown Timer

- Fits single-gang box
- 120 VAC, 9 Amp Max.
- For use with all Broan fans within Amp rating



Model MS100W (White)
Occupancy Sensor

- Fits single-gang box
- LED/CFL 300W, Incandescent 600W, 1/2 HP, 120 VAC, 9 Amp Max. (Fan + Light)
- For use with all Broan fans within Amp rating




Model DD500W (White)
Digital Dehumidistat

- Fits single-gang box
- 120 VAC, 9 Amp Max.
- For use with all Broan fans within Amp rating



Model P2RW (White)
2 Rocker Switch

- Two, independent, 120 VAC, 15 Amp rocker switches
- Can be used in a 15 amp or 20 amp branch circuit
- Fits single-gang box
- For use with all Broan fans and heaters within Amp rating




Model DT100W (White)
Delay Off Timer

- Fits single-gang box
- 120 VAC, 6 Amp Max. (3 A Fan + 3 A Lamp)
- For use with all Broan fans within Amp rating




Model P3RW (White)
3 Rocker Switch

- Three, independent, 120 VAC, 15 Amp rocker switches
- Can be used in a 15 amp or 20 amp branch circuit
- Fits single-gang box
- For use with all Broan fans and heaters within Amp rating




Model SC100W (White)
Speed Control

- Fits single-gang box
- 120 VAC, 3 Amp Max.
- For use only with Broan fans that can be used with speed controls and within Amp rating




**69W (White)
Single-Function Control**

- Fits single-gang box
- 120 VAC, 15 Amp
- For use with all Broan fans within Amp rating



**Model 80L
Electronic Speed Control (Internal)**

- Specially designed for use with Broan LoSone Select® ventilators rated at 3 Amps or less
- Metal housing
- 3 A, 120 VAC, 60 Hz




**Model 71V (Ivory)
12-Hour Timer**

- Operates continuously or for any set period up to 12 hours
- Fits single-gang box
- 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
- For use with all Broan fans and heaters within Amp rating




**Model 82W (White), 82A (Light Almond)
Premium Humidity Sensing Wall Control**

- Sensaire™ technology detects rising humidity to react to showers and clear mirrors quickly
- Variable setting from 20% to 80% relative humidity
- Can be used to comply with California Title 24 and CALGreen
- Precise sensitivity adjustment
- Continuous ventilation mode operates fan set minutes per hour to meet ASHRAE 62.2
- User-adjustable automatic shutoff timer
- LED indicator and manual operation mode
- Fits single-gang box
- 120 VAC, 60 Hz
- Requires neutral wire for operation.



**Model 72V (Ivory), 72W (White)
Electronic Variable Speed Control (6 Amp)**

- Rotary dial for variable selection of fan speed and sound level
- Positive on/off action
- Fits single-gang box
- Built-in radio noise suppressor
- Switched wire included for additional use if desired (120 VAC, 6 Amp)
- For use with all Broan fans within Amp rating except ceiling paddle fans
- Do not use with impedance protected motor




**Model 269VL (Ivory), 269WL (White)
Two-Function Control with Indicator**

- Red light indicates power is on
- Specially designed for use with Broan Solitaire® Ultra Silent™ fans and an auxiliary light source
- Fits two-gang box
- 120 VAC, 20 Amp lighted switch; 120/240/277 VAC, 15 Amp unlighted switch


**Model 75V (Ivory)
Electronic Variable Speed Control (6 Amp)**

- 240 VAC, 6 Amp capacity
- For use with Broan Model L3500EXL LoSone® Select™ Cabinet Ventilator
- Other features same as Model 72V




**685WL (White)
Three-Function Control with Indicator**

- Red light indicates power is on
- Specially designed for use with Broan Solitaire® Ultra Silent™ fans /lights
- Fits two-gang box
- 120 VAC, 20 Amp lighted switch; 120 VAC, 15 Amp each unlighted switch (20 Amp total)




**Model 77DV (Ivory), 77DW (White)
Four-Function Control**

- Specially designed for use with Broan SensAire® and Designer Series fan/ lights
- Separate switches control fan (on/off/ auto), light (on/off), and night-light (on/ off)
- 120 VAC, Amps each rocker = 15, 15, 5 (20 Amp total)
- Fits single-gang opening
- Includes switch function labels




**Model DH100W
Dehumidistat**


- Fits single-gang box
- Variable setting from 20% to 80% relative humidity
- Dual voltage (24V/120V)
- Usage guide included




- Model 57V (Ivory), 57W (White)
Electronic Variable Speed Control (3 Amp)**
- Rotary dial for variable selection of fan speed and sound level
 - Positive off position
 - Fits single-gang box
 - Built-in radio noise suppressor
 - 120 VAC, 3.0 Amp capacity
 - For use with all Broan fans within Amp rating except ceiling paddle fans
 - Do not use with impedance protected motor




- Model 63V (Ivory), 63W (White)
60-Minute Time Control with Rocker Switch**
- One, independent 120 VAC, 15 Amp rocker switch
 - Timer has same features as Model 62V/62W
 - For use with all Broan fans and heaters within Amp rating




- Model 59V (Ivory), 59W (White)
60-Minute Time Control**
- Operates continuously or for any set period up to 60 minutes
 - Fits single-gang box
 - 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
 - Also recommended for low voltage (30V Max) applications
 - For use with all Broan fans and heaters within Amp rating




- Model 64V (Ivory), 64W (White)
Fan/Light Control with Off-Delay**
- Fan and light operate together when control is turned on. Fan continues to operate for a set time period (user adjustable from 1-60 minutes) after light is turned off
 - Center position turns fan and light off immediately
 - Can also be used with a fan only
 - Fits single-gang box
 - 120 VAC, 4 Amp (fan) and 4 Amp (light) capacity
 - For use with all Broan fans and fan/lights within Amp rating. Requires both sides of the electrical line (hot & neutral) in the switchbox



- Model 61V (Ivory), 61W (White)
15-Minute Time Control**
- Operates for any set period up to 15 minutes (no "continuous on" position)
 - Fits single-gang box
 - 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
 - Also recommended for low voltage (30V Max) applications
 - For use with all Broan fans and heaters within Amp rating




- Model 66V (Ivory), 66W (White)
Three-Function Control with Plastic Wall Plate**



- Model 62W (White)
60-Minute Time Control
with Two Rocker Switches**
- Two, independent, 120 VAC, 15 Amp rocker switches (20 Amp Total)
 - Timer operates continuously or for any set period up to 60 minutes
 - Fits two-gang box
 - 120 VAC, 20 Amp or 240 VAC, 10 Amp timer capacity
 - For use with all Broan fans and heaters within Amp rating

- Model 67W (White)
Three-Function Control with Chrome Finish
Metal Wall Plate**

- Three, independent, 120 VAC, 15 Amp rocker switches (20 Amp total)
- Fits single-gang opening
- For use with all Broan fans and heaters within Amp rating



- Model 68V (Ivory), 68W (White)
Two-Function Control**
- Two, independent, 120 VAC, 15 Amp rocker switches (20 Amp total)
 - Fits single-gang box
 - For use with all Broan fans and heaters within Amp rating