TECHNICAL DATA SHEET

DAP[®] All-Purpose Stucco Patch (Dry Mix)

PRODUCT DESCRIPTION

DAP[®] All-Purpose Stucco Patch may be used to repair large holes and cracks in interior and exterior stucco surfaces. It's easy to mix formula blends naturally with existing stucco for a professional finish. Durable and permanent. Easy to tool and paint. Interior/exterior use.



PACKAGING	COLOR	UPC
25 lb. bag	White	7079810502

KEY FEATURES & BENEFITS

- Professional quality, for repairs in stucco surfaces
- Easy to tool and paint
- Durable
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on stucco

APPLICATION

- 1. Surface must be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
- 2. Add stucco patch to clear water in clean container mixing 4 parts of powder to 1 part of water by volume. For a smoother finish, dip putty knife in water and lightly smooth spackling.
- 3. Let the mixture set for 15 minutes then re-stir until smooth. Do not mix more material than can be used in 1 to 2 hours. Discard any material that has begun to harden.



4. Apply stucco patch with a clean putty knife or trowel. For fills over 1/4" deep apply 2 or more layers allowing each layer to dry before applying the next layer. Use a rubber float to blend patch with the existing stucco surface.

NOTE: Consult paint manufacturer's recommendations before decorating.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Working Time	1 to 2 hours	
Setting Time	2 to 4 hours	
Final Cure	3 days	
Mixing Ratio	Add 5 pt. water to 25 lb. bag Stucco Patch	
Coverage	10-12 sq. ft. with ¼" thickness	

CLEAN UP & STORAGE

- Wash skin and hands with soap and water.
- Cured material must be scraped or sanded away.
- Wash tools with water immediately after use.
- Be sure bag is closed and tightly sealed.
- Store powder in a cool, dry place.
- Do not store mixed material.