



TECHNICAL DATA SHEET

DAP® All Purpose Stucco Patch (Ready Mix)

PRODUCT DESCRIPTION

DAP® All-Purpose Stucco Patch may be used to repair small holes and cracks in interior and exterior stucco surfaces. It's ready to use sanded formula blends naturally with existing stucco for a professional finish.



PACKAGING	COLOR	UPC
Quart	White	7079810504
Gallon	White	7079860590

KEY FEATURES & BENEFITS

- For repairing small holes and cracks in stucco surfaces
- Durable and permanent
- Textured finish
- Ready to use
- Easy to tool and paint
- Interior/exterior use

SUGGESTED USES

For patching small holes and cracks in stucco surfaces.

FOR BEST RESULTS

- Consult paint manufacturer's recommendations before decorating. To repair large breaks, cracks and holes in stucco surfaces, use DAP Stucco Patch Dry Mix.
- Can be painted after final cure (3 days).
- **DO NOT USE AS A SKIM COAT.**



TECHNICAL DATA SHEET

APPLICATION

1. Surface must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
2. Apply stucco patch with a clean putty knife or trowel. For fills over 1/4" deep, apply 2 or more layers allowing each layer to dry before applying the next one.
3. Use a rubber float to blend patch with the existing stucco surface.
4. Store the tightly sealed container in a cool, dry place for re-use.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Setting Time:	2 to 4 hours
Final Cure:	3 Days
Odor:	Mild
Consistency:	Coarse, thick paste
Vehicle:	Latex emulsion
Volatile:	Water
Filler:	Calcium carbonate, sand
Solids:	84 ± 1.0% by weight
Weight per Gallon:	15.6 lbs./gal.
Shelf Life:	12 months
Coverage:	1 qt./946 mL 12-18 sq. ft.
	1 gal. 48-72 sq. ft. NOTE: These figures are approximate and may vary with job site conditions

CLEAN UP & STORAGE

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.