



TECHNICAL DATA SHEET

DAP® FAST 'N FINAL® Lightweight Spackling

PRODUCT DESCRIPTION

DAP® FAST 'N FINAL® **Lightweight Spackling** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint in minutes. It is easy to apply with one strike of the putty knife. Won't shrink or crack. Ideal for repairing holes, cracks and dents in drywall, plaster, wood and stucco. DAP FAST 'N FINAL Lightweight Spackling is low in odor and for interior or exterior use.



PACKAGING	COLOR	UPC
2.8 oz.	White	7079812317
½ Pint	White	7079812140
Pint	White	7079812141
Quart	White	7079812142
Gallon	White	7079812143

KEY FEATURES & BENEFITS

- **Patch & Prime in One Step**
- **Fast Drying – 30-minute Paint Ready**
- **No Sanding**
- **Won't Sink or Shrink**
- **Interior/Exterior use**

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on: Drywall, Plaster, Wood, Stucco, Brick.

FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.



TECHNICAL DATA SHEET

- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, first apply exterior-grade primer, then apply spackling and finish with coating of quality exterior-grade paint.
- Do not use for tuck pointing applications on brick

APPLICATION

1. Surface must be free of grease, oil and other foreign matter.
2. Stir thoroughly before use.
(When using the 2.8 oz tube, remove top, grip tube bottom & twist up a very small amount (about 1/16") of filler. Either apply directly to surface or using built-in spackling knife, scrape off spackling from top of tube & apply to wall)
3. Using a clean putty knife, press spackling into hole or crack.
4. Draw blade firmly across the surface to remove excess material in one strike.
5. For a smoother finish, dip putty knife into water and lightly smooth spackling.
6. One application is usually sufficient for small repairs.
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
7. May be painted within minutes with a latex paint. Please follow paint manufacturer's instructions for application.
8. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Paint	Takes either oil or latex-based paint
Solids	75% by solids
Application Temperature	40°F or higher



TECHNICAL DATA SHEET

Service Temperature	-20°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	30 minutes depending on temperature, humidity and depth of fill

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be removed by scraping or sanding. Be sure container lid/cap is closed and tightly sealed and store in a cool, dry place away from extreme heat or cold.