



# TECHNICAL DATA SHEET

## DAP® KWIK SEAL ULTRA® Advanced Siliconized Sealant - Clear

### PRODUCT DESCRIPTION

DAP® KWIK SEAL ULTRA® ADVANCED KITCHEN & BATH SEALANT is formulated with innovative ultra-hydrophobic technology that repels water, dirt and stains and offers a lifetime mold and mildew resistance guarantee so the sealant stays looking clean, fresh and new. It is 100% waterproof and crack proof and can be exposed to water in as little as 4 hours after application without washing out. KWIK SEAL ULTRA has strong multi-surface adhesion and excellent flexibility for long lasting durability. Safe for granite and marble. The easy-to-use formula applies easily, tools smoothly, is low in odor and cleans up with water. Interior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300 mL) Cartridge	Clear	7079818898
5.5 fl oz (162 mL) Tube	Clear	7079818895

### KEY FEATURES & BENEFITS

- Ultra-hydrophobic technology repels water, dirt, soap scum and stains
- Lifetime mold & mildew resistance guarantee
- Sealant stays looking clean, fresh & new
- 100% waterproof, crack proof & stain proof
- 4 hour water ready
- Strong, multi-surface adhesion
- Easy application: easy gunning and smooth tooling
- Easy water clean-up & low odor
- Safe for granite & marble
- VOC compliant
- Interior use



# TECHNICAL DATA SHEET

## SUGGESTED USES

### USE FOR CAULKING & SEALING:

- Tubs
- Showers
- Sinks
- Backsplashes
- Vanities
- Countertops
- Fixtures
- Pipes
- Repairing loose tiles

### ADHERES TO:

- Wood – painted & unpainted
- Ceramic
- Porcelain
- Glass
- Most metals
- Most plastics
- Fiberglass
- Drywall
- Plaster
- Granite
- Cultured marble
- Brick
- Stone
- Most common building materials

## FOR BEST RESULTS

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer rod material.
- **Sealant applies white and dries clear in 7-14 days depending on joint depth, temperature and humidity.**
- **Wait 4 hours before exposing to water.**
- Regular cleaning of surrounding areas is suggested.
- Store sealant away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all old caulk, dirt and other foreign material. Rubbing alcohol (Isopropyl alcohol) is recommended for removing soap film and soil.

### Product Application

1. If using the squeeze tube, remove cap.
2. Cut nozzle at 45° angle to desired bead size.
3. If using the cartridge, load into caulk gun.
4. Fill gap or joint with sealant.
5. If necessary, tool or smooth the bead of sealant with a finishing tool before sealant skins over.
6. **Sealant applies white and dries clear in 7-14 days depending on joint depth, temperature and humidity.**



# TECHNICAL DATA SHEET

7. Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant must be cut or scraped away. Clean hands and tools with warm water and soap.
8. Allow sealant to dry at least 4 hours (longer in cool or humid conditions) before exposing to water.
9. Reseal container for storage and reuse.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

<b>Typical Uncured Physical Properties</b>	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Acrylic copolymer
Filler	Not applicable
Volatile	Water
Weight % Solids	58%
Density (lbs per gallon )	8.6
Odor	Very mild
Clean Up	Water
Flash Point	>212°F
Freeze Thaw Stability (ASTM C1183)	Passes 5 Cycles
Shelf Life	12 months
Coverage	10.1 fl oz: 55 linear feet at a 3/16" diameter bead 5.5 fl oz: 30 linear feet at 3/16" diameter bead
<b>Typical Application Properties</b>	
Application Temperature Range	40°F to 100°F
Tooling Time (Working Time)	5 minutes
Tack Free Time	10 minutes
Full Dry Through	7-14 days
Return to Service Time	4 hours
Vertical Sag (ASTM D2202)	0.05"
<b>Typical Cured Performance Properties</b>	
Service Temperature Range	0°F to 170°F
Water Ready Time	4 hours
Paint Ready Time	Not paintable
Mildew Resistance	Lifetime mold & mildew resistance



# TECHNICAL DATA SHEET

## CLEAN UP & STORAGE

Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant must be cut or scraped away. Clean hands and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.