



TECHNICAL DATA SHEET

DAP® PLASTIC WOOD® Wood Putty

PRODUCT DESCRIPTION

DAP® PLASTIC WOOD® Wood Putty is an easy-to-use, non-hardening wood putty that quickly repairs holes and minor defects in prefinished interior surfaces after assembly and finishing. Colors can be blended for custom color matching. Interior use only.



PACKAGING	COLOR	UPC
3.7 oz	White	7079821245
3.7 oz	Cherry	7079821250
3.7 oz	Dark Walnut	7079821255
3.7 oz	Ebony	7079821266
3.7 oz	Light Oak	7079821247
3.7 oz	Light Walnut	7079821251
3.7 oz	Maple	7079821270
3.7 oz	Natural Oak	7079821276
3.7 oz	Natural Pine	7079821272
3.7 oz	Pickled Oak	7079821274
3.7 oz	Red Mahogany	7079821268
3.7 oz	Red Oak	7079821262

KEY FEATURES & BENEFITS

- Fills holes and minor defects
- Non-hardening
- Color matched to most wood finishes
- Interior use only

SUGGESTED USES

Ideal for quick repairs of minor scratches, gouges, nail holes and other minor imperfections on interior surfaces such as:



TECHNICAL DATA SHEET

- Baseboards
- Paneling
- Cabinets
- Woodwork
- Molding
- Furniture
- Windows/Doors
- Other wood surfaces

APPLICATION

1. Surface to be filled must be clean and dry. Surface, wood putty and air temperature should be 40°F or higher. Product cannot be painted, stained or coated.
2. Stain, seal or topcoat surface before applying wood putty.
3. Press DAP PLASTIC WOOD Wood Putty firmly into nail holes or other imperfections.
4. Avoid excess contact with surrounding area. Wipe excess putty from surrounding area with a cloth rag or towel.
5. Wood Putty will not harden to a sand able surface.
6. Most repairs require just one fill. Deep holes may require more than one application.
7. Colors can be blended for custom matches. Test color match on scrap or inconspicuous area prior to application.

FOR BEST RESULTS

- This product is designed to be applied as a final finish.
- This product is not stainable, sandable or paintable.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	Knife-Grade Putty
Vehicle	Blend of vegetable and mineral oils
Filler	Inorganic Fillers and Color Pigments
Volatile	Aliphatic Hydrocarbons
Solids	99% by weight
Weight per Gallon	18 lbs.



TECHNICAL DATA SHEET

Odor	Mild, pleasant
Shelf Life	24 months
Application Temperature	40°F Minimum
Dry Time	24 to 36 Hours

CLEAN UP & STORAGE

Clean tools immediately after use with mineral spirits. Do not use mineral spirits to clean skin. Be sure container lid is closed and tightly sealed. Store upside down in a cool, dry place away from extreme heat or cold.