



TECHNICAL DATA SHEET

DAP® Ready Mixed Concrete Patch

PRODUCT DESCRIPTION

DAP® Ready Mixed Concrete Patch is a ready to use material for the repair of holes, cracks, and other imperfections in concrete or masonry surfaces. The product is excellent for tuck pointing masonry and brick work. It may also be used as a “glue” to join broken pieces of concrete or brick. **DO NOT USE AS A SKIM COAT.** The material dries to a concrete-gray color.



PACKAGING	COLOR	UPC
Quart	Gray	7079831084
Gallon	Gray	7079831090

KEY FEATURES & BENEFITS

- Repairs cracks and breaks in concrete and masonry
- Durable and non-shrinking
- Can be used to spot level

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on concrete.

APPLICATION

1. Use a wire brush, chisel, or similar tool to remove all loose material, dust, dirt, oil and grease from the area to be repaired. Use a solvent to remove oil and grease. Rough up the surface one or two inches beyond the area to be repaired for a good bond. Dampen the area with clean water – **DO NOT FLOOD.**
2. Stir the patch to a smooth consistency; no thinning is required. With a flexible putty knife, broad knife, or trowel fill in the area to be repaired, pressing compound firmly into holes or cracks.
3. If area to be patched is deeper than 1/2 inch, apply patch in 1/4-inch layers, maximum depth 1 inch, allowing each application to dry.



TECHNICAL DATA SHEET

4. If used as a “glue,” apply at least one layer of concrete patch to both surfaces to be repaired. Push the pieces together and use bracing or weights to support the assembly during cure.
5. Patched areas may be painted with a quality latex paint after 2 to 4 hours or alkyd paint after 24 hours if desired.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Paste
Vehicle	Latex Emulsion
Solid Content	83% +/- 1%
Application Temperature	Temperatures greater than 40°F
Drying Time	Allow to dry 24 hours before driving over patched area. Do not apply if rain is likely within drying period or if temperature is apt to drop below 40°F
Paintable	Yes, 2 to 4 hours, longer if humidity is high.
Shelf Life	12 months

CLEAN UP & STORAGE

Clean hands and tools with soap and water. Dry material must be chiseled or scraped away. Keep from freezing. Close container tightly after each use.