SAFETY DATA SHEET		dicor proc	ducts
SECTION 1 - PRODUCT AND COM PRODUCT NAME: Fiberglass Roof Coaing PRODUCT CODE: RP-FRC GENERAL USE: Fiberglass roof coating	PANY IDENTIFIC	CATION	
PRODUCT DESCRIPTION: Pigmented acrylic emulsion COMPANY NAME Dicor Corporation			V
SECTION 2 - HAZARDS ID	ENTIFICATION		
ROUTES OF EXPOSURE			MIS Codes
INHALATION of vapor or spray mist. EYE or SKIN contact with the product, vapor or spray mist.		Health Flammability	1
EFFECTS OF OVEREXPOSURE	3	Reactivity	0
Irritation.		Protective Equipment	E
SIGNS AND SYMPTOMS OF OVEREXPOSURE			
Redness and itching or burning sensation may indicate eye or excessive skill MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	n exposure.		
None generally recognized.			
SECTION 3 - COMPOSITION / INFORM	ATION ON INGE	REDIENTS	
HAZARDOUS COMPONENT	CAS #	% By Weight	
PROPYLENE GLYCOL	57-55-6	1.14	
TITANIUM DIOXIDE	13463-67-7	6.40	
CALCIUM CARBONATE	1317-65-3	30.90	
ACRYLIC POLYMER EMULSION	SUPP. CONF.	36.70	
WATER	7732-18-5	14.86	
			Th
SECTION 4 - FIRST AID	MEASURES		
SECTION 4 - FIRST AID ROUTES OF EXPOSUBE: Inhalation of vanor or mist. Eve or skin		luct vapor or mist	
ROUTES OF EXPOSURE: Inhalation of vapor or mist. Eye or skin	contact with the proc	-	
ROUTES OF EXPOSURE: Inhalation of vapor or mist. Eye or skin EYES: Flush eyes with large amounts of water	contact with the proc r for 15 minutess. Ge	-	
ROUTES OF EXPOSURE: Inhalation of vapor or mist. Eye or skin	a contact with the proc r for 15 minutess. Ge oap and water.	t medical attention.	

ON .
GIH TLV WT %
NE 1.14
mg / m ³ 6.40
mg / m ³ 30.90
NE 36.70
NE 14.86

SKIN PROTECTION Wear impervious gloves and apron to prevent skin contact.

EYE/FACE PROTECTION

Use splash-proof safety googles or face shield.

OTHER PRECAUTIONS

Eyewash station and safety shower should be available within the workplace.

ENGINEERING CONTROLS

Local exhaust preferable. General exhaust is acceptable if maintained below applicable exposure limits.

SECT	ION 9 - PHYSICAL AND CHEMICAL PROPERTIES
PHYSICAL STATE	Liquid
	Non-descript
COLOR	
BOILING POINT	8.5 to 9.0
FREEZING POINT	
FLAMMABILITY	
RELATIVE DENSITY	1.36
SOLUBILITY	
VOC CONTENT	
MATERIALS TO AVOID	SECTION 10 - STABILITY AND REACTIVITY
None	
HAZARDOUS REACTIONS	
Stable HAZARDOUS POLYMERIZATION	
Will not occur	ECTION 11 - TOXICOLOGICAL INFORMATION
ACUTE EFFECTS	ECTION TT-TOXICOLOGICAL INFORMATION
None known	
CRYSTALLINE SILICAS	
Exposures to respirable Crystalline sil	ica are not expected during normal use of this product. Prolonged and repeated exposure
	silica can result in lung disease (silicosis) and/or lung cancer. The risk of developing
silicosis is dependent upon the expo	
	SECTION 12 - ECOLOGICAL INFORMATION
ECOLOGICAL EFFECTS This product has no known adverse e	cological effects
	SECTION 13 - DISPOSAL CONSIDERATIONS
Collect and dispose of in accordance	with Federal, State/Provincial and Local
Do not contaminate ground water and	
Recycle empty buckets or bags.	
	SECTION 14 - TRANSPORT INFORMATION
Non - regulated, not classified as dang	
	SECTION 15 - REGULATORY INFORMATION
Observe the general safety regulation	s when nandling.
SARA 313 Not considered hazardous	
EPCRA 302 Not considered hazardou	IS.
EPCRA 304 Not considered hazardou	IS.
RCRA Hazardous Waste: Not Listed	
	SECTION 16 - OTHER INFORMATION
This product is not intended for use in foo	o or pharmaceuticais.
The information provided in this Safety I	Data Sheet is, to the best of our knowledge, correct. The data set forth on this sheet is based on
	f raw materials and chemicals used in the production and manufacture of the aforementioned
	varranty with respect to the accuracy of the information provided by the suppliers, and disclaims
all liability or reliance thereof. Buyer as	sumes all risk of use, storage and handling of the product in accordance with federal, state and
local laws and regulations.	

Rely on premium RV roofing and sealants by Dicor if you're looking for quality and efficiency.