

Application: ACRYLIC COATING must be preceded with DICOR CLEANER/ACTIVATOR to ensure proper adhesion. All cleaner/activator must be completely removed from roof prior to applying acrylic coating. All surfaces must be clean and free of residue or loose particles, degraded substrate, grease, oil, dirt, or other contaminants. Surfaces shall be completely dry and frostfree before coating. Deteriorated or damaged substrates shall be repaired or replaced.

Apply after using the cleaner/activator with a medium nap roller or brush. One gallon covers up to 125 sq. ft. Actual gallons required will depend on the type of surface and texture, method of application and weather conditions at the time of application. Surfaces must be uniformly coated and free from voids, pinholes and blisters. Two coats required.

NOTE: Entire 2 part project must be completed in one day; including cleaner/activator application, rinsing and 2 coats of CoolCoat™ each dry to the touch.

Preparation: Thoroughly mix the contents for a minimum of 15 minutes prior to application. DICOR ACRYLIC COATING may be applied by medium nap roller or brush. Clean equipment with water and a universal cleaner.

CAUTION: CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS; CAN CAUSE NAUSEA AND HEADACHE. Prolonged or repeated breathing of vapor or spray mist may be harmful. Use a respirator for protection from vapor or spray mist. Avoid eye and skin contact. Do not take internally. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use.

Contains: Aqueous Acrylic Emulsions, Calcium Carbonate (471-34-1), Aluminum Trihydroxide (1645-51-2), Titanium Dioxide (13463-67-7)

KEEP FROM FREEZING • USE ONLY IN A WELL VENTILATED AREA

CAUTION: KEEP OUT OF REACH OF CHILDREN