

Application: Signature Extended Life RV Roof Coating™ must be preceded with DICOR CLEANER/ACTIVATOR (RP-CRP-Q) to ensure proper adhesion. All cleaner/activator must be completely removed from roof prior to applying acrylic coating. All surfaces must be clean and free of residue or loose particles, degraded substrate, grease, oil, dirt, or other contaminants. Surfaces shall be completely dry and frostfree before coating. Deteriorated or damaged substrates must be repaired or replaced. Signature Extended Life RV Roof Coating™ shall be applied in a minimum of 2 coats at a rate of 1 gallon per 125 sq. ft per coat (i.e. 8' X 30' roof takes 4 gallons). Actual gallons required will depend on the type of surface and texture, method of application, and weather conditions at the time of application. All surfaces must be uniformly coated and free from voids, pinholes, or blisters. Apply between 32°-120°F. Two hour cure time. Dries to touch in one hour, walkable in two. Let first layer dry to touch prior to starting second coat. Must be completed in one day. Do not apply if rain is expected within four hours of last coat.

Preparation: Thoroughly mix the contents for a minimum of 5 minutes prior to application. Signature Extended Life RV Roof Coating™ may be applied by medium nap roller or brush. Clean equipment with water and a universal cleaner.

CAUTION: CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS; CAN CAUSE NAUSEA AND HEADACHE. Prolonged or repeated breathing of vapor or spray mist may be harmful. Use a respirator for protection from vapor or spray mist. Avoid eye and skin contact. Do not take internally. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use. Slip Warning: Use extreme caution when walking and working on silicone coated roofs.

Contains: Silanol Terminated Polydimethylsiloxane (70131-67-8), Crystalline Silica (14808-60-7) Titanium Dioxide (13463-67-7)

USE ONLY IN A WELL VENTILATED AREA

CAUTION: KEEP OUT OF REACH OF CHILDREN

MAINTENANCE: If your RV roof is coated with our Signature Extended Life RV Roof Coating™ and you wish to apply lap sealant, please [contact](#) Dicor customer service for the best solution for your application needs.