

ELECTRIC PRODUCT COMPARISONS

iE-11

iE-18

iE-24

iE-27



SPECIFICATIONS

	iE-11	iE-18	iE-24	iE-27
INSTALLATION	INDOOR ONLY	INDOOR ONLY	INDOOR ONLY	INDOOR ONLY
Rated GPM	1.8 Gallons per Minute	2.5 Gallons per Minute	3 Gallons Per Minute	3.5 Gallons per minute
Voltage	240	240	240	240
Kilowatt	15kw	18kw	24kw	27kw
Max Amp. Load	50	75	100	113
Min. Req. Circuit Breaker	60	2x50	3x40	3x50
Wire Size (AWG)	#8	#8	#8	#8
Temperature Control	Automatic 86° - 140°F	Automatic 86° - 140°F	Automatic 86° - 140°F	Automatic 86° - 140°F
Temp Rise	1 GPM - 52°F	1 .25 GPM - 80°F	1.5 GPM - 80°F	1.75 GPM - 80°F
Temp Rise	1.8 GPM - 35°F	2.5 GPM - 40°F	3 GPM - 40°F	3.5 GPM - 40°F
Temp Rise	2.8 GPM - 17°F	3.75 GPM - 20°F	4.5 GPM - 20°F	5.5 GPM - 20°F
Warranty	2 year limited	2 year limited	2 year limited	2 year limited
Product Dimensions	19.75"x10.75"x3.25" - 25 lbs	19.75"x10.75"x3.25" - 25 lbs	19.75"x10.75"x3.25" - 26 lbs	19.75"x10.75"x3.25" - 27 lbs
Suggested Uses	1 to 2 single use applications	apartment, cottages, whole home, 2 applications in warmer climates	whole home up to 3 applications	whole home, multiple applications