

# WHOLE HOME PRODUCT COMPARISONS

## FVI12

## i12

## 45H

## 45HI



**SPECIFICATIONS**

	FVI12	i12	45H	45HI
INSTALLATION	INDOOR ONLY	INDOOR ONLY	OUTDOOR ONLY	INDOOR ONLY
BTU	74,000	80,000	140,000	140,000
Flow Rate	3.6 GPM	3.0 GPM	6.8 GPM	6.8 GPM
Portable	No	No	No	No
Voltage	110/120	110/120	110/120	110/120
Gas Type	Available in NG & LP	Available in NG & LP	Available in NG & LP	Available in NG & LP
Venting	2.5" horizontal Venting (Incl)	2.5" horizontal Venting (Incl)	Not Needed	Sold Separately
Water Pressure	20-80 PSI	20-80 PSI - Flow activated	20-80 PSI - Flow Activated	20-80 PSI - Flow Activated
Regulator & Hose	Not Included	Not Included	Not included	Not Included
Temperature Control	Manual 80° - 120°F	Automatic 80° - 120°F	Automatic 90° - 140°F	Automatic 90° - 140°F
Warranty	2 Years limited	2 Years limited	10 Years - Heat Exchanger 5 Years - Parts	10 Years - Heat Exchanger 5 Years - Parts
Product Dimensions	15" x 4" x 24" - 30 lbs	14" x 5" x 24" - 30 lbs	15" x 5" x 24" - 38 lbs	15" x 5" x 24" - 38 lbs
Package Dimensions	17" x 11" x 28" - 32 lbs	17" x 11" x 29" - 32 lbs	16" x 7.5" x 26" - 40 lbs	16" x 7.5" x 26" - 40 lbs