


PLUG-IN EXPLOSIVE GAS AND CARBON MONOXIDE ALARM WITH BATTERY BACK-UP AND SILENCE FEATURE



120VAC ~ 60Hz, 0.25 A

IMPORTANT! PLEASE READ CAREFULLY AND SAVE.

This user's manual contains important information about your Smoke Alarm's operation. If you are installing this Smoke Alarm for use by others, you must leave this manual—or a copy of it—with the end user.

Printed in Mexico
M08-0123-013 K1 5/16

CONFORMS TO UL STD
1484 and UL STD 2034

Model GC01

BASIC SAFETY INFORMATION

IMPORTANT!

- Dangers, Warnings, and Cautions alert you to important operating instructions or to potentially hazardous situations. Pay special attention to these items.

⚠ CAUTION!

- This combination Explosive Gas/Carbon Monoxide Alarm has two separate alarms. The CO Alarm is not designed to detect fire or any other gas. It will only indicate the presence of carbon monoxide gas at the sensor. Carbon monoxide gas may be present in other areas. The Explosive Gas Alarm will only indicate the presence of explosive gas that reaches the sensor. The Explosive Gas Alarm is not designed to sense smoke, heat or flames.
- Do not stand too close to the unit when the alarm is sounding. It is loud to wake you in an emergency. Exposure to the horn at close range may harm your hearing.
- Do not paint over the unit. Paint may clog the openings to the sensing chambers and prevent the unit from operating properly.

⚠ WARNING!

- This unit must be powered by a 24-hour circuit. Be sure the circuit cannot be turned off by a switch, dimmer, or ground fault circuit interrupter. Failure to connect this unit to a 24-hour circuit may prevent it from providing constant protection.
- This Alarm must have AC or battery power to operate. If AC power fails and the battery is dead or missing, the alarm cannot operate.
- The Alarm will check for the presence of explosive gas at the sensor less frequently when powered by the back-up battery. Explosive gas could be present during the period between checks without going into alarm, especially during a condition that results in a rapid buildup of explosive gas.
- Test the Alarm once a week. If the Alarm ever fails to test correctly, have it replaced immediately! If the Alarm is not working properly, it cannot alert you to a problem.
- This combination Carbon Monoxide and Explosive Gas Alarm is intended for residential use and is not suitable for use in hazardous locations as defined in the National Electrical Code.
- This product is intended for use in ordinary indoor locations of family living units. It is not designed to measure CO levels in compliance with Occupational Safety and Health Administration (OSHA) commercial or industrial standards. Individuals with medical conditions that may make them more sensitive to carbon monoxide may consider using warning devices which provide audible and visual signals for carbon monoxide concentrations under 30 ppm. For additional information on carbon monoxide and your medical condition contact your physician.

FCC Compliance

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate, radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that the interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that of the receiver.
- Consult the dealer or an experienced radio or TV technician for help.

Warning: Changes or modifications to the product, not expressly approved by First Alert / BRK Brands, Inc., could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

INSTALLATION

WHERE TO INSTALL THIS ALARM

For Gas Alarms, mounting depends on the type of explosive gas you intend to detect.

Natural Gas (methane) is typically supplied through a main utility line connected to your home. If you do not live in a rural area you are likely to be a user of natural gas. Natural gas is a fossil fuel consisting mainly of Methane. Methane is much lighter than air and will rise rapidly in air. If you are a user of natural gas, the Alarm should be mounted between 6 and 12 inches (152mm and 305 mm) away from the ceiling (using cord feature) to ensure the earliest opportunity to detect a leak.

Propane is typically supplied to homes by delivery truck in liquid form and stored near the home in propane tanks. Propane is used by homes in rural areas that do not have natural gas service. Since propane is the most commonly used Liquefied Petroleum Gas (LPG), **propane** and **LP-Gas** are often used synonymously. Unlike natural gas, propane is heavier than air and will collect at lower levels. If you are a user of propane, the Alarm should be mounted near the floor (using the direct plug-in feature) to ensure the earliest opportunity to detect a leak.

Both propane and natural gas are colorless and odorless. For safety reasons, an odorant (Mercaptan) is added so that any leak can be detected by smell. The common detection threshold for smelling the gases is around 20% of the **Lower Explosion Limit (LEL)**. This can vary greatly depending on the individuals sense of smell and how long they have been exposed to it. The LEL of each of these gases defines the bottom range of flammability for the gas. Your Alarm is calibrated to sound before 25% of the LEL of either gas detected.

Therefore, it is possible that you may smell gas before the Alarm is activated. If you are not sure which gas your home uses, contact your utility company.

For CO Alarms, the National Fire Protection Association (NFPA) recommends that a CO Alarm should be centrally located outside of each separate sleeping area in the immediate vicinity of the bedrooms. For added protection, install additional CO Alarms in each separate bedroom, and on every level of your home.


In general, install combination Explosive Gas and Carbon Monoxide Alarms:

- **WHERE YOU CAN HEAR THE ALARM FROM ALL SLEEPING AREAS**
- In or near bedrooms and living areas or wherever you suspect a gas or CO exposure is likely.
- On each level of a multi-level home.

IMPORTANT!

Improper location can affect the sensitive electronic components in this Alarm. Please see "Where this Alarm Should Not Be Installed".

Recommended Placement



See "Avoiding Dead Air Spaces" for more information.

NOTE: For any location, make sure no door or other obstruction could keep carbon monoxide or gas from reaching the Alarm.

⚠ WARNING!

This unit should receive continuous electrical power. (The battery is meant for emergency back-up only). Choose an outlet where it can't be accidentally unplugged or switched off by children. Keep small children away from the unit. Teach them not to play with it or unplug it. Explain what the alarms mean.

WHERE THIS ALARM SHOULD NOT BE INSTALLED

To avoid causing damage to the unit, to provide optimum protection, and to prevent unnecessary alarms, Do NOT locate this Alarm:

- In garages, kitchens, crawl spaces and unfinished attics. Avoid extremely dusty, dirty or greasy areas. Installation in these areas could lead to nuisance alarms, may expose the sensor to substances that could damage or contaminate it, or the Alarm may not be heard by persons in other areas of the home, especially if they are sleeping.
- In the garage, vehicle exhaust can contain some carbon monoxide. These levels are higher when the engine is first started. Within hours of starting a vehicle and backing it out of the garage, the levels present over time can activate the Alarm and become a nuisance.
- In the kitchen, some gas appliances can emit a short burst of CO or gas upon start-up. This is normal. If your Explosive Gas/CO Alarm is installed too close to these appliances, it may alarm often and become a nuisance.
- Keep units at least 20 feet (6 meters) from the sources of combustion particles (stove, furnace, water heater, space heater) if possible. In areas where a 20-foot (6m) distance is not possible – in modular, mobile, or smaller homes, for example – it is recommended the Alarm be placed as far from these fuel-burning sources as possible. The placement recommendations are intended to keep these Alarms at a reasonable distance from a fuel-burning source, and thus reduce “unwanted” alarms. Unwanted alarms can occur if an Alarm is placed directly next to a fuel-burning source. Ventilate these areas as much as possible. **If you must install the Alarm near a cooking or heating appliance, install at least 5 feet (1.5 meters) from appliance.**
- In extremely humid areas. This Alarm should be at least 10 feet (3 meters) from a shower, sauna, humidifier, vaporizer, dishwasher, laundry room, utility room, or other source of high humidity.
- In direct sunlight.
- In turbulent air, like near ceiling fans or open windows. Blowing air may prevent CO or gas from reaching the sensors.
- In areas where temperature is colder than 40° F (4.4° C) or hotter than 100° F (37.8° C). These areas include non-airconditioned crawl spaces, unfinished attics, uninsulated or poorly insulated ceilings, porches, and garages.
- Less than 12 inches (305 mm) away from fluorescent lights. Electrical “noise” can interfere with the sensor.
- In “dead air” spaces. See “Avoiding Dead Air Spaces”.

AVOIDING DEAD AIR SPACES

“Dead air” spaces may prevent gas from reaching the Alarm. To avoid dead air spaces, follow installation recommendations below.

On ceilings, install Alarms as close to the center of the ceiling as possible. If this is not possible, install the Alarm at least 4 inches (102 mm) from the wall or corner.

For wall mounting, the top edge of Alarms should be placed between 6 inches (152 mm) and 12 inches (305 mm) from the wall/ceiling line.

On a peaked, gabled, or cathedral ceiling, install Alarm within 3 feet (0.9 meters) of the peak of the ceiling, measured horizontally.

BEFORE YOU BEGIN INSTALLATION

Since CO generally mixes well with air, mounting the Alarm will depend on the type of explosive gas you intend to detect. If you are not certain which type of gas you are using in your home, please read about natural gas and propane in “Where to Install this Alarm”.

⚠ WARNING!

- **Make sure the alarm is not receiving excessively noisy power. Examples of noisy power could be major appliances on the same circuit, power from a generator or solar power, light dimmer on the same circuit or mounted near fluorescent lighting. Excessively noisy power may cause damage to your Alarm.**

Find the pair of self-adhesive labels included with this Gas/CO Alarm.

- On each label write in the phone number of your emergency responder (like 911) and a qualified appliance technician.
- Place one label near the Gas/CO Alarm, and the other label in the “fresh air” location you plan to go if the alarm sounds.

HOW TO INSTALL THIS GAS/CO ALARM

IMPORTANT! Read all instructions before using this product.

Tools you will need: Screwdriver, drill.

1. Determine the best location for your Gas/CO Alarm.
2. Your Alarm is equipped to be mounted as a corded unit (recommended for natural gas detection), a direct plug unit (recommended for propane gas detection). The unit can be plugged directly into a wall outlet. If your outlets are mounted horizontally, refer to “If Outlet is Mounted Horizontally (Sideways)”

If the adapter is taken out of the unit, the Alarm can be installed high on the wall, while the adapter is plugged into a wall outlet. The explosive gas you use will determine if the Alarm should be installed high on the wall (AC cord option) or low on the wall (direct plug option).

ACTIVATING THE BATTERY BACK-UP

IMPORTANT!

Activate the battery back-up by installing the battery. The battery is for back-up only and is not intended to power the Alarm for an extended period of time in the absence of AC.

The Alarm will light-up the display briefly to indicate the unit is receiving power.

DIRECT PLUG ALARM INTO AN OUTLET (FOR PROPANE DETECTION)

IMPORTANT!

This Alarm can be plugged directly into a wall outlet located close to the floor. This is the recommended configuration for detecting propane.

1. Choose a standard UNSWITCHED 120V AC outlet.
2. Plug Alarm in.

IF OUTLET IS MOUNTED HORIZONTALLY (SIDEWAYS)

If you are going to use your Alarm as a direct plug into an outlet that is mounted horizontally (sideways), you may want to **rotate the adapter 90°**, as follows:

1. With back of unit facing you (AC blades on your left), place your left thumb on adapter release and grab AC blades with your right hand to release the left side.
2. Repeat for the other side adapter thumb release. This will allow adapter to slide out.
3. Remove adapter.
4. Rotate the adapter 90° and snap firmly back into place.
5. Plug Alarm into AC outlet.

WALL MOUNTED ALARM (FOR NATURAL GAS DETECTION)

IMPORTANT!

Installation tips for power cord models: The power cord option provides more flexibility in mounting locations and allows the Alarm to be easily installed at or above eye level.

NOTE: If you mount the Alarm high on a wall, make sure it is **between 6 to 12 inches (152-305 mm) down from the ceiling**. Any higher than this, it will be in “dead air” space and carbon monoxide or natural gas may not reach the sensors.

NOTE: Do not cover the Alarm with a curtain.

To install for a wall-mount, you will need to pull out the removable adapter and power cord, as follows:

1. Repeat steps 1 to 3 as described above in “to rotate the adapter”.
2. With adapter out, pull out power cord and unwrap it.
3. Insert the screws provided until head is approx. 1/8 inch (3 mm) from wall (if mounting in plaster board or drywall, drill 3/16 inch (5 mm) hole and use plastic anchor provided). Use mounting guide template to locate holes as shown in diagram below.
4. Hook the Alarm over the screw onto the keyhole in back of unit.
5. Plug power cord into AC outlet.

SECURING THE POWER CORD TO AN OUTLET

⚠ WARNING!

1. Remove the wallplate screw from the outlet and hold the wallplate in position.
2. Plug the power cord into the wall outlet so that the screw hole lines up with the wallplate screw hole.
3. Insert the screw through the power cord screw hole and into the wallplate screw hole.
4. Tighten screw in place and restore power to the outlet.


TEST THE ALARM

1. Make sure the Alarm is receiving AC power. Under normal operation, the Green indicator light will shine continuously. If the Green power indicator light does not light, recheck connections. If connections are correct and the Green power indicator still does not light, the unit should be replaced immediately.
2. Press and hold the test button until the alarm sounds. You will hear the signal that indicates the presence of explosive gas followed by the signal for carbon monoxide.

When testing the Alarm, have someone else check that the Alarm can be heard easily from the sleeping areas. The unit should be located where it can wake you if it alarms at night.

HOW YOUR ALARM WORKS

THE COVER OF YOUR ALARM



1. Test/Silence Button: Press and hold to activate test, or to silence the alarm.
2. POWER Light (GREEN)
3. Display
4. (Behind the Cover) Alarm Horn: 85 dB audible alarm for test, alarm, and unit malfunction warning.
5. Display Button: Press to recall highest CO level recorded
6. Battery Compartment

IF YOUR GAS/CO ALARM SOUNDS WHAT TO DO IF CARBON MONOXIDE IS DETECTED ▲WARNING!

Actuation of your CO Alarm indicates the presence of carbon monoxide (CO) which can kill you. In other words, when your CO Alarm sounds, you must not ignore it!

IF THE CO ALARM SOUNDS:

- Operate the Test/Silence button.
- Call your emergency services, fire department or 911. Write down the number of your local emergency service here:

- Immediately move to fresh air—outdoors or by an open door or window. Do a head count to check that all persons are accounted for. Do not re-enter the premises, or move away from the open door or window until the emergency services responder has arrived, the premises have been aired out, and your CO Alarm remains in its normal condition.
- After following steps 1-3, if your CO Alarm reactivates within a 24-hour period, repeat steps 1-3 and call a qualified appliance technician to investigate for sources of CO from fuel-burning equipment and appliances, and inspect for proper operation of this equipment. If problems are identified during this inspection have the equipment serviced immediately. Note any combustion equipment not inspected by the technician, and consult the manufacturers' instructions, or contact the manufacturers directly, for more information about CO safety and this equipment. Make sure that motor vehicles are not, and have not, been operating in an attached garage or adjacent to the residence. Write down the number of a qualified appliance technician here:

WHAT TO DO IF EXPLOSIVE GAS IS DETECTED

If you hear the alarm horn sound one beep per second, gas has been detected. The word GAS will be displayed. Evacuate everyone from the building.

- Leave the house immediately, opening doors and windows as you leave.
- Do not use your telephone or appliances. Do not turn any light switches off or on. Any spark or flame could ignite the gas.
- Call 911 and your gas company from a phone that is away from your home.
- Do not re-enter the area until the source of the leak is found and corrected.

▲WARNING!

- If the unit alarms and you are not testing the unit, it is warning you of a potentially dangerous situation that requires your immediate attention. NEVER ignore any alarm. Ignoring the alarm may result in injury or death.
- Never disconnect the power to quiet an unwanted alarm. Disconnecting the power disables the Alarm. This will remove your protection.

▲WARNING!

Alarms have various limitations. See "General Limitations of Explosive Gas/CO Alarms" for details.

USING THE SILENCE FEATURES

▲WARNING!

NEVER disconnect the power to your Alarm to silence the horn—use the Silence Feature. Disconnecting the Alarm removes your protection!

- The Silence Feature is intended to temporarily silence the horn while you identify and correct the problem.
- To use the Silence Feature, press the Test/Silence button until the horn is silent.
- If the Test/Silence button is pressed while the Alarm is in the silence mode, the alarm will start sounding again.

When the GAS Alarm is silenced...

The Alarm will remain silent for approximately 2 minutes and then return to normal operation. If the gas has not cleared within the silence period, the unit will go back into alarm.

When the CO Alarm is silenced...

The CO Alarm will remain silent for up to 4 minutes. While the Alarm is silenced, it will continue to monitor the air for CO. After 4 minutes, if CO levels remain potentially dangerous the horn will start sounding again.

IMPORTANT!

The Silence Feature is intended to temporarily silence the Alarm horn. It will not correct a CO or gas problem.

SILENCING THE LOW BATTERY WARNING

This Silence Feature can temporarily quiet the low battery warning "chirp" for up to 8 hours if AC power is present. You can silence the low battery warning "chirp" by pressing the Test/Silence button on the Alarm cover until you see the Green LED flicker, acknowledging the button-press.

The display will flash "SILENCE" for 8 hours while the low battery warning "chirp" silence feature is activated. After 8 hours, the low battery "chirp" will resume. The Alarm will continue to operate as long as AC power is supplied. However, **replace the battery as soon as possible**, to maintain protection in event of a power outage.

SILENCING THE END OF LIFE SIGNAL

This silence feature can temporarily quiet the End of Life warning "chirp" for up to 2 days. You can silence the End of Life warning "chirp" by pressing the Test/Silence button. The horn will chirp, acknowledging that the End of Life silence feature has been activated.

After approximately 2 days, the End of Life "chirp" will resume.

USING THE PEAK CO MEMORY

The CO Memory Feature lets you check the highest level of CO recorded.

To check CO Memory:

- Press the Display button until the peak CO level is displayed.









To clear CO Memory:

- Automatically resets after 24 hours.
- While checking CO memory, press or hold the Display button until "CLEAR" is displayed.
 - Press or hold the Display button until the CO Memory is cleared.
- Remove all power; unplug the Alarm and remove the battery.



NOTE: The highest CO level will be saved for 24 hours. DO NOT clear the CO Memory reading if you plan to call someone to investigate a CO problem! Clear the CO Memory reading only after the investigator has checked your home. If the investigator will not arrive within the 24 hour time period before the unit automatically resets, be sure to write down the peak level.

UNDERSTANDING THE LIGHT, HORN, AND DISPLAY PATTERNS

Condition	LED	Horn	Display
NORMAL AC POWER	LED is Green	Silent	All segments of display are turned on for a short time upon initial power. Then the battery level icon is displayed. 
BATTERY BACK-UP POWER	LED is Off, flashing Green once every 45 seconds	Silent	All segments of display are turned On for a short time upon initial power. Then the battery level icon is displayed flashing.
DURING TESTING	LED flashes Red in sync with the horn, simulating an Alarm condition: first gas then CO	First, the horn pattern for gas alarm (1 beep every second) is issued, and then the CO alarm horn pattern (4 beeps, pause, 4 beeps) is issued.	During the simulated gas alarm, "GAS" is displayed along with a full alarm level. During the simulated CO alarm, "CO" is displayed along with a full alarm level. Several ppm CO levels are also displayed and the alarm level is shown increasing. 
LOW OR MISSING BATTERY	Normal	A chirp is issued about every minute.	Battery icon will show either 1 bar or an empty icon. 
GAS ALARM CONDITION	LED flashes Red in sync with horn	Repeating 1 beep every second	"GAS", a full level, and "EVACUATE" 
CARBON MONOXIDE ALARM	LED flashes Red in sync with horn	Repeating 4 beeps, pause	"CO" alternating with the ppm number, a full level, and "EVACUATE". 
PRE-ALARM CONDITION CO IS PRESENT	Normal	Normal	"CO" alternating with the ppm number. The level will indicate relative CO exposure level.
MALFUNCTION	LED flashing Green 3 times in sync with 3 chirps	3 chirps every minute	"Err" is displayed. 
LOW BATTERY SILENCE	LED is Green	Silent	"bat" and "SILENCE" are displayed. 
END OF LIFE	LED flashing Green 5 times in sync with 5 chirps	5 chirps every minute	"End" is displayed. 

REGULAR MAINTENANCE

This unit has been designed to be as maintenance-free as possible, but there are a few simple things you must do to keep it working properly:

- Test it at least once a week.
- Clean the Alarm at least once a month; gently vacuum the outside of the Alarm using your household vacuum's soft brush attachment. Test the Alarm. Never use water, cleaners or solvents since they may damage the unit.
- Relocate the unit if it sounds frequent unwanted alarms. See "Where This Alarm Should Not Be Installed" for details.
- When the battery back-up becomes weak, the Alarm will "chirp" about once a minute (the low battery warning). You should replace the battery immediately to continue your protection.

This Alarm must have AC or battery power to operate. If AC power fails, and the battery is dead or missing, the Alarm cannot operate.

▲WARNING!

DO NOT spray cleaning chemicals or insect sprays directly on or near the Alarm. DO NOT paint over the Alarm. Doing so may permanently damage the Alarm.

CHOOSING A REPLACEMENT BATTERY:

Your Alarm requires one standard 9V alkaline battery. The following batteries are acceptable as replacements: Duracell® #MN1604, (Ultra) #MX1604; Eveready (Energizer) #522. **These batteries are available at many local retail stores.**

▲WARNING!

- Always use the exact batteries specified by this User's Manual. DO NOT use rechargeable batteries. Clean the battery contacts and also those of the device prior to battery installation. Install batteries correctly with regard to polarity (+ and -).
- Please dispose of or recycle used batteries properly, following any local regulations. Consult your local waste management authority or recycling organization to find an electronics recycling facility in your area. DO NOT DISPOSE OF BATTERIES IN FIRE. BATTERIES MAY EXPLODE OR LEAK.

▲WARNING!

- Keep battery out of reach of children. In the event a battery is swallowed, immediately contact your poison control center, your physician, or the National Battery Ingestion hotline as serious injury may occur.

IMPORTANT!

Actual battery service life depends on the Alarm and the environment in which it is installed. All the batteries specified above are acceptable replacement batteries for this unit. Regardless of the manufacturer's suggested battery life, you MUST replace the battery immediately once the unit starts "chirping" (the "low battery warning").

WHAT YOU NEED TO KNOW ABOUT CO

WHAT IS CO?

CO is an invisible, odorless, tasteless gas produced when fossil fuels do not burn completely, or are exposed to heat (usually fire). Electrical appliances typically do not produce CO.

These fuels include: Wood, coal, charcoal, oil, natural gas, gasoline, kerosene, and propane.

Common appliances are often sources of CO. If they are not properly maintained, are improperly ventilated, or malfunction, CO levels can rise quickly. CO is a real danger now that homes are more energy efficient. "Air-tight" homes with added insulation, sealed windows, and other weatherproofing can "trap" CO inside.

SYMPTOMS OF CO POISONING

These symptoms are related to CO POISONING and should be discussed with ALL household members.

Mild Exposure: Slight headache, nausea, vomiting, fatigue ("flu-like" symptoms).

Medium Exposure: Throbbing headache, drowsiness, confusion, fast heart rate.

Extreme Exposure: Convulsions, unconsciousness, heart and lung failure. Exposure to Carbon Monoxide can cause brain damage, death.

▲WARNING!


Some individuals are more sensitive to CO than others, including people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. Members of sensitive populations should consult their doctors for advice on taking additional precautions.

FINDING THE SOURCE OF CO AFTER AN ALARM


Carbon monoxide is an odorless, invisible gas, which often makes it difficult to locate the source of CO after an alarm. These are a few of the factors that can make it difficult to locate sources of CO:

- House well ventilated before the investigator arrives.
- Problem caused by "backdrafting."
- Transient CO problem caused by special circumstances.

Because CO may dissipate by the time an investigator arrives, it may be difficult to locate the source of CO. **BRK Brands, Inc. shall not be obligated to pay for any carbon monoxide investigation or service call.**



POTENTIAL SOURCES OF CO IN THE HOME



Fuel-burning appliances like: portable heater, gas or wood burning fireplace, gas kitchen range or cooktop, gas clothes dryer.

Damaged or insufficient venting: corroded or disconnected water heater vent pipe, leaking chimney pipe or flue, or cracked heat exchanger, blocked or clogged chimney opening.

Improper use of appliance/ device: operating a barbecue grill or vehicle in an enclosed area (like a garage or screened porch).

Transient CO Problems: "transient" or on-again-off-again CO problems can be caused by outdoor conditions and other special circumstances.

The following conditions can result in transient CO situations:

- Excessive spillage or reverse venting of fuel appliances caused by outdoor conditions such as:
 - Wind direction and/or velocity, including high, gusty winds. Heavy air in the vent pipes (cold/humid air with extended periods between cycles).
 - Negative pressure differential resulting from the use of exhaust fans.
 - Several appliances running at the same time competing for limited fresh air.
 - Vent pipe connections vibrating loose from clothes dryers, furnaces, or water heaters.
 - Obstructions in or unconventional vent pipe designs which can amplify the above situations.
- Extended operation of unvented fuel burning devices (range, oven, fireplace).
- Temperature inversions, which can trap exhaust close to the ground.
- Car idling in an open or closed attached garage, or near a home.

These conditions are dangerous because they can trap exhaust in your home. Since these conditions can come and go, they are also hard to recreate during a CO investigation.

HOW CAN I PROTECT MY FAMILY FROM CO POISONING?

A Gas/CO Alarm is an excellent means of protection. It monitors the air and sounds a loud alarm before Carbon Monoxide levels become threatening for average, healthy adults.

A Gas/CO Alarm is not a substitute for proper maintenance of home appliances.

To help prevent CO problems and reduce the risk of CO poisoning:

- Clean chimneys and flues yearly. Keep them free of debris, leaves, and nests for proper air flow. Also, have a professional check for rust and corrosion, cracks, or separations. These conditions can prevent proper air movement and cause backdrafting. Never "cap" or cover a chimney in any way that would block air flow.
- Test and maintain all fuel-burning equipment annually. Many local gas or oil companies and HVAC companies offer appliance inspections for a nominal fee.
- Make regular visual inspections of all fuel-burning appliances. Check appliances for excessive rust and scaling. Also check the flame on the burner and pilot lights. The flame should be blue. A yellow flame means fuel is not being burned completely and CO may be present. Keep the blower door on the furnace closed. Use vents or fans when they are available on all fuel-burning appliances. Make sure appliances are vented to the outside. Do not grill or barbecue indoors, or in garages or on screen porches.
- Check for exhaust backflow from CO sources. Check the draft hood on an operating furnace for a backdraft. Look for cracks on furnace heat exchangers.
- Check the house or garage on the other side of shared wall.
- Keep windows and doors open slightly. If you suspect that CO is escaping into your home, open a window or a door. Opening windows and doors can significantly decrease CO levels.

In addition, familiarize yourself with all enclosed materials. Read this manual in its entirety, and make sure you understand what to do if your Gas/CO Alarm sounds.

REGULATORY INFORMATION FOR EXPLOSIVE GAS/CO ALARMS REGULATORY INFORMATION FOR CO ALARMS UNDERWRITERS LABORATORIES INC. UL2034

WHAT LEVELS OF CO CAUSE AN ALARM?

Underwriters Laboratories Inc. Standard UL2034 requires residential CO Alarms to sound when exposed to levels of CO and exposure times as described below. They are measured in parts per million (ppm) of CO over time (in minutes).

UL2034 Required Alarm Points*:

- If the alarm is exposed to 400 ppm of CO, IT MUST ALARM BETWEEN 4 and 15 MINUTES.
- If the alarm is exposed to 150 ppm of CO, IT MUST ALARM BETWEEN 10 and 50 MINUTES.
- If the alarm is exposed to 70 ppm if CO, IT MUST ALARM BETWEEN 60 and 240 MINUTES.

Approximately 10% COHb exposure at levels of 10% to 95% Relative Humidity (RH).

The unit is designed not to alarm when exposed to a constant level of 30 ppm for 30 days.

IMPORTANT!

CO Alarms are designed to alarm before there is an immediate life threat. Since you cannot see or smell CO, never assume it's not present.

- An exposure to 100 ppm of CO for 20 minutes may not affect average, healthy adults, but after 4 hours the same level may cause headaches.
- An exposure to 400 ppm of CO may cause headaches in average, healthy adults after 35 minutes, but can cause death after 2 hours.

IMPORTANT!

This CO Alarm measures exposure to CO over time. It alarms if CO levels are extremely high in a short period of time, or if CO levels reach a certain minimum over a long period of time. The CO Alarm generally sounds an alarm before the onset of symptoms in average, healthy adults.

Why is this important? Because you need to be warned of a potential CO problem while you can still react in time. In many reported cases of CO exposure, victims may be aware that they are not feeling well, but become disoriented and can no longer react well enough to exit the building or get help. Also, young children and pets may be the first affected. The average healthy adult might not feel any symptoms when the CO Alarm sounds. However, people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. If you experience even mild symptoms of CO poisoning, consult your doctor immediately!

Standards: Underwriters Laboratories Inc. Single and Multiple Station carbon monoxide alarms UL2034.

According to Underwriters Laboratories Inc. UL2034, Section 1-1.2: "Carbon monoxide alarms covered by these requirements are intended to respond to the presence of carbon monoxide from sources such as, but not limited to, exhaust from internal-combustion engines, abnormal operation of fuel-fired appliances, and fireplaces. CO Alarms are intended to alarm at carbon monoxide levels below those that could cause a loss of ability to react to the dangers of Carbon Monoxide exposure." This CO Alarm monitors the air at the Alarm, and is designed to alarm before CO levels become life threatening. This allows you precious time to leave the house and correct the problem. This is only possible if Alarms are located, installed, and maintained as described in this manual.

Gas Detection at Typical Temperature and Humidity Ranges: The CO Alarm is not formulated to detect CO levels below 30 ppm typically. UL tested for false alarm resistance to Methane (500 ppm), Butane (300 ppm), Heptane (500 ppm), Ethyl Acetate (200 ppm), Isopropyl Alcohol (200 ppm) and Carbon Dioxide (5000 ppm). Values measure gas and vapor concentrations in parts per million.

Audible Alarm: 85 dB minimum at 10 feet (3 meters).

REGULATORY INFORMATION FOR EXPLOSIVE GAS ALARMS

Standards: Underwriters Laboratories Inc. UL1484.

According to Underwriters Laboratories Inc. UL1484, this unit meets the alarm response time for gas as follows: This unit shall alarm before 25% of the LEL of either natural gas or propane is detected. In all cases, the unit will detect gas as a priority over carbon monoxide. If the device is detecting CO, then detects an amount of gas to cause an alarm, the device will stop alarming for CO and begin to alarm for gas.

GENERAL LIMITATIONS OF EXPLOSIVE GAS/CO ALARMS

This Gas/CO Alarm is intended for residential use. It is not intended for use in industrial applications where Occupational Safety and Health Administration (OSHA) requirements for Carbon Monoxide Alarms must be met. This device is not intended to alert hearing impaired residents.

Gas/CO Alarms may not waken all individuals. If children or others do not readily waken to the sound of the Gas/CO Alarm, or if there are infants or family members with mobility limitations, make sure that someone is assigned to assist them in the event of an emergency.

This Gas/CO Alarm will not sense gas or CO that does not reach the sensors. It will only sense gas or CO at the sensor. Gas or CO may be present in other areas. Doors or other obstructions may affect the rate at which CO or gas reaches the sensors.

Gas/CO Alarms may not be heard. The alarm horn loudness meets or exceeds current UL standards of 85 dB at 10 feet (3 meters). However, if the Gas/CO Alarm is installed outside the bedroom, it may not wake up a sound sleeper or one who has recently used drugs or has been drinking alcoholic beverages. This is especially true if the door is closed or only partly open. Even persons who are awake may not hear the alarm horn if the sound is blocked by distance or closed doors. Noise from traffic, stereo, radio, television, air conditioner, or other appliances may also prevent alert persons from hearing the alarm horn. This Gas/CO Alarm is not intended for people who are hearing impaired.

This Gas/CO Alarm is not a substitute for life insurance. Though this Gas/CO Alarm warns against increasing CO levels or the presence of gas, BRK Brands, Inc. does not warrant or imply in any way that they will protect lives. Homeowners and renters must still insure their lives.

This Gas/CO Alarm is not foolproof. Like all other electronic devices, this Gas/CO Alarm has limitations. It can only detect gas or CO that reaches the sensors. It may not give early warning of the source of gas or CO is in a remote part of the home, away from the alarm device.

This Gas/CO Alarm has a limited life. Although this Gas/CO Alarm and all of its parts have passed many stringent tests and are designed to be as reliable as possible, any of these parts could fail at any time. Therefore, you must test this device weekly. The unit should be replaced immediately if it is not operating properly.

TROUBLESHOOTING GUIDE

If your Alarm does this...	It means...	You should...
Green light is OFF. Unit will not alarm when you press the Test/Silence button.	Unit may not be receiving any power.	Check the AC power supply. Make sure a fresh 9V battery is installed to power the battery back-up.
Green light flashes ON, once a minute (horn is silent).	Alarm is not receiving AC power. Unit is operating on battery back-up.	Check the AC power supply.
The horn "chirps" once a minute.	Low battery warning. Battery is low or missing.	Replace the battery. Avoid interrupting AC power.
Once a minute, the alarm sounds 3 "chirps", and the green light flashes three times.	MALFUNCTION SIGNAL. Based on its Self Test diagnostics, the unit has detected a malfunction. The unit needs to be replaced.	Units under warranty should be returned to manufacturer for replacement. See "Limited Warranty" for details.
The light flashes (Green) and the horn sounds 5 "chirps" every minute.	END OF LIFE SIGNAL. Alarm needs to be replaced	Immediately replace the Alarm.
The horn sounds constantly with no pattern and cannot be silenced,	Unit malfunction. Unit needs to be replaced.	Units under warranty should be returned to manufacturer for replacement. See "Limited Warranty" for details.
Alarm goes back into alarm after you pressed the Test/Silence button to silence an alarm.	Gas and/or CO levels are still potentially dangerous.	Refer to "If Your Gas/CO Alarm Sounds" for details on how to respond to an alarm. If anyone is feeling ill, EVACUATE your home immediately and call 911.
Alarm sounds frequently even though no high levels of gas or CO are revealed in an investigation.	Alarm sounds frequently even though no high levels of gas or CO are revealed in an investigation.	Relocate your alarm. If frequent alarms continue, have home rechecked for potential problems. You may be experiencing an intermittent gas or CO problem.
*For a list of acceptable replacement batteries, see "Regular Maintenance."		