



FEATURES & BENEFITS

- 3 Year Warranty
- Formulated to renew existing roof surfaces
- Reflects heat & harmful UV rays
- Protects against the elements, extending the life of the roof



PRODUCT DESCRIPTION

Kool Seal RV™ Elastomeric Finish Coat (KSRV08300) is formulated to renew existing roof surfaces; reflects heat and harmful UV rays; and protects against the elements, extending the life of the roof. Three Year Warranty.

RECOMMENDED USES

- Metal, EPDM and other single ply membranes, modified bitumen, polyurethane foam, concrete, rubber roofs and previously coated surfaces.
- Do NOT use over asphalt shingles or silicone coatings.

ORDERING INFORMATION

Part Number	Color/Size
KSRV08300-16	White (1-Gallon)

PRODUCT CHARACTERISTICS

Vehicle	100% Acrylic
Color	White
Volume Solids	36% ± 2%
Weight Solids	50% ± 2%
VOC	< 50 g/L
Drying Time	Exposure to rain or heavy dew: 4-6 hours Between coats and before foot traffic: 24 hours minimum

Dry time is temperature, humidity and film thickness dependent

COVERAGE RATES

Apply at 50-100 sq. ft. per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended. EPDM rubber roofs must be primed with Kool Seal RV Elastomeric Gray Base Coat (Refer to KSRV08210 for coverage rate).

DO NOT DILUTE THIS PRODUCT.



SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

Surface must be power washed (minimum 2,000 psi) to remove dirt, and other foreign matter which could prevent proper adhesion. Surfaces must be completely dry prior to coating. Repair all cracks, breaks, open seams and other imperfections with Kool Seal® Storm Patch® Acrylic Patching Cement and Kool Seal Storm Patch Polyester Fabric. Apply Kool Seal Storm Patch Acrylic Rust Primer to existing rusted areas. Kool Seal RV Elastomeric Finish Coat must be applied over Kool Seal RV Elastomeric Gray Base Coat for all EPDM rubber roofs to ensure proper adhesion (Refer to KSRV08120 data sheet for surface preparation).

APPLICATION

Do not apply below 50°F (10°C) or when rain is forecast. Applications during periods of low temperature and high humidity will extend dry time. Humidity of 85% or more will drastically increase drying time. In areas where dew accumulates in early evening, it is best to coat in the morning. NOTE: Stop coating by early afternoon (3 p.m.) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries KEEP FROM FREEZING.

Thoroughly mix product prior to application. Two coats of finish coat recommended. Airless spray or apply with a low nap roller or broom at the appropriate coverage rate Always apply two coats in different directions. Apply the first coat in a north-south direction, the second in an eastwest direction. For spray application, an airless pump is recommended. Pump one gallon per minute with at least 2,000 P.S.I. fluid pressure. Suggested tip sizes are .021 with a 10" pattern or .025 with a 12" pattern. Allow adequate drying time between coats.

CLEANUP

Warm, soapy water

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

LIMITED WARRANTY

For 3 years from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferable. This warranty excludes failure due to improper surface preparation, structural defects, or failure of other previously applied products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

TECHNICAL SERVICES

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.