

Battery Disconnects

Intellitec's Battery Disconnects provide a simple, reliable, and cost effective means of remotely disconnecting the battery of larger vehicles or boats. Rather than having to install long runs of heavy, unprotected battery cable to a large cumbersome switch, the Disconnect can be located near the battery, out of normal reach. It is connected to a low current switch conveniently located for the driver by a low current cable. The concern of long battery cables shorting to the chassis is all but gone.

The Battery Disconnect is designed incorporating Intellitec's patent No. 4,628,289, of a simple magnetic mechanism. It operates as a latching relay, drawing NO current to keep it closed or open. This latching feature allows the Disconnect to operate without discharging the battery.

To close the Disconnect, a positive voltage is applied to the unmarked terminal of the coil and the negative of the supply is connected to the "S" terminal, for a brief period. When the power is removed, the relay is latched in the "on" or closed position. Current can now flow through the large terminals.

The Disconnect is ignition protected, so it can safely be mounted in a convenient place near the battery. It can be mounted in any orientation. It is immune to harsh shake and vibration found in the vehicle or marine environment.

The Disconnect in a typical installation, is mounted near the vehicle battery to keep the length of the battery cables to a minimum. Keeping these wires short adds to the safety of the installation and helps minimize the cost. The wires to the Disconnect's coil are run to a remote switch, usually located at a convenient location near an entry door. Additional switches can be wired to allow operation of the Disconnect from multiple locations, such as the front and rear of a vehicle. If required, Intellitec can provide a complete solution with disconnect, switch and harnessing to suit most applications

The Intellitec battery disconnects are available in both 12 & 24V versions and in 100A & 250A continuously rated options



Battery Disconnects

Part Numbers

Part No	01-00055-002	01-00055-242	01-00056-000	01-00056-024
Specification	100A 12V	100A 24V	250A 12V	250A 24V
Actuation current	3.0A	1.2A	3.0A	1.2A
Min actuation voltage	9.0V	18V	9.0V	18V
Max continuous carry current	100A	100A	250A	250A
Max short term carry current (30 secs)	500A	500A	TBD	TBD
Ambient temperature	-40 to + 85C	-40 to + 85C	-40 to +85C	-40 to +85C
Contact life at full load	Min 10,000 cycles	Min 10,000 cycles	Min 10,000 cycles	Min 10,000 cycles
Max actuation time	0.2 seconds	0.2 seconds	0.2 seconds	0.2 seconds