



FEATURES & BENEFITS

- Satisfaction Guaranteed
- Excellent adhesion to most roofing surfaces
- Premium base layer for Kool Seal RV™ Elastomeric Finish Coats



PRODUCT DESCRIPTION

Kool Seal RV™ Elastomeric Base Coat (KSRV08120) is formulated to provide excellent adhesion to most surfaces and a premium base layer for Kool Seal RV™ Elastomeric Finish Coats. Kool Seal RV™ Elastomeric Base Coat is light gray in color, allowing for easy application of Kool Seal® Elastomeric Finish Coats. Satisfaction Guaranteed.

RECOMMENDED USES

- Designed for EPDM rubber roofs
- Can also be used on metal, EPDM and other single ply membranes, modified bitumen, polyurethane foam, concrete, and previously coated surfaces.
- Do NOT use over asphalt shingles or silicone coatings.

ORDERING INFORMATION

Part Number	Color/Size
KSRV08120-14	Light Gray (1-Quart)
KSRV08120-16	Light Gray (1-Gallon)

PRODUCT CHARACTERISTICS

Vehicle	100% Acrylic
Color	Light Gray
Volume Solids	33% ± 2%
Weight Solids	43% ± 2%
VOC	< 50 g/L
Drying Time	Exposure to rain or heavy dew: 4-6 hours Between coats and before foot traffic: 24 hours minimum

Dry time is temperature, humidity and film thickness dependent

COVERAGE RATES

Apply at 50-100 sq. ft. per gallon per coat. Rough/porous surfaces will require additional coating. Two coats recommended. Must be top coated with Kool Seal RV Elastomeric Finish Coats.

DO NOT DILUTE THIS PRODUCT.



SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

Surface must be power washed (minimum 2,000 psi) to remove dirt, and other foreign matter which could prevent proper adhesion. Surfaces must be completely dry prior to coating. Repair all cracks, breaks, open seams and other imperfections with Kool Seal® Storm Patch® Acrylic Patching Cement and Kool Seal Polyester Fabric. Apply Kool Seal Storm Patch Acrylic Rust Primer to existing rusted areas. Kool Seal RV Elastomeric Gray Base Coat must be top coated with Kool Seal RV Elastomeric Finish Coat.

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

APPLICATION

Do not apply below 50°F (10°C) or when rain is forecast. Applications during periods of low temperature and high humidity will extend dry time. Humidity of 85% or more will drastically increase drying time. In areas where dew accumulates in early evening, it is best to coat in the morning. NOTE: Stop coating by early afternoon (3 p.m.) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries KEEP FROM FREEZING.

Thoroughly mix product prior to application. Airless spray or apply with a low nap roller or broom at the appropriate coverage rate. For spray application, an airless pump is recommended. Pump one gallon per minute with at least 2,000 P.S.I. fluid pressure. Suggested tip sizes are .021 with a 10" pattern or .025 with a 12" pattern. Allow adequate drying time between coats.

CLEANUP

Warm, soapy water