



Digital Media



FEATURES:

- Receive over-the-air TV broadcasts when connected to an antenna source
- Digital ATSC tuner
- Watch TV when and how you like with time-shift recording (requires USB drive, not included)
- Analog pass-through connection supports legacy TV broadcasts
- Enjoy digital media from USB memory drives
- HD and standard definition video output
- RF antenna connections
- Accessories included: AC power adapter, Remote Control, Battery, A/V cable, User manual
- Product Dimensions: 5.13" x 4.00" x 1.26"

* For more detailed information about this product including set up information, please download the Setup sheet for this item from the Naxa site.

* Features, specifications, measurements and weights may be subject to change without prior notice.



Features

- Receive over-the-air TV broadcasts when connected to an antenna source
- Digital ATSC tuner
- Watch TV when and how you like with time-shift recording (requires USB drive, not included)
- Analog pass-through connection supports legacy TV broadcasts
- Enjoy digital media from USB memory drives
- HD and standard definition video output
- RF antenna connections
- Accessories included: AC power adapter, Remote control, Battery, A/V cable, User manual

Product Details

Model

NT-54

Unit

Dimensions (in): 5.13 x 4 x 1.26 [L x W x H]

Weight (lbs): 0.28

Giftbox/Clamshell

Dimensions (in): 7.6 x 6 x 2 [L x W x H]

Weight (lbs): 0.9

Master Carton

Of Units/per: 10

Dimensions (in): 12.7 X 10.8 X 8.4 [L x W x H]

Weight (lbs): 9.98

Loading Qty/Container

20: 15240

40: 26120

40HQ: 31520

Specifications

- **TV Tuner:** ATSC, NTSC
- **Removable Memory Support:** USB 2.0 (NTFS, FAT32, FAT16)
- **Playable Media Formats:** Music: MP3, AAC, Video: MPEG-2, MPEG-4, H.264, MJPEG, Photo: JPEG, BMP, PNG
- **Video Format Support:** MPEG-2, MPEG-4, H.264, MJPEG
- **Image Format Support:** JPEG, BMP, PNG
- **Input Sources:** Coaxial RF antenna
- **Output:** HD video (up to 1080p), Composite video + audio, Coaxial RF pass through
- **Multi-Language:** English, Spanish
- **Power Source:** AC 100-240V (DC 5V, 1.5A)
- **UL/ETL Certification :** Yes