Progressive Industries

Smart Surge Protector (SSP)
SSP-30XL & SSP-50XL (UL)

Operating Guide for:

Model SSP-30XL

Rated at 120V

and

Model SSP-50XL

Rated at 120/240V



SSP-30XL & SSP-50XL Instructions

INSTALL STEPS:

STEP 1: Plug Smart Surge Protector into AC power. **DO NOT** plug in your RV at this time. **Verify GREEN** surge indicator LED(s) is on.

STEP 2: Verify which LED's come on. The Correct Wiring condition occurs when both the GREEN and BLUE LED's are on (See Diagram (A)). If this does not occur you may be experiencing one of the other three (3) Wiring Conditions as noted in the diagrams.


- **B** Reverse Polarity
- (C) Open Neutral
- (D) Open Ground

Your Smart Surge Protector will continue to work during any of the wiring conditions; however, only the **Correct Wiring** condition (both **GREEN** & **BLUE** LED's on) is optimal and any other wiring condition should be corrected by Campground Maintenance before use.

STEP 3: Plug in your RV power to the Smart Surge Protector. Refer to STEP 2 above for surge protection wiring conditions.

FEATURES INCLUDE:

3-Color LED Indicator Lights, Weather Resistant, Dual Line Polarity Tester (SSP-50XL only), Pull Handle on Plug, Lifetime Warranty, it's portable, just plug it in and like with all our products its made in the USA!



SPECIFICATIONS:

SSP-30XL

Rated at 120V

Joule Rating: 825J Surge Amps: 22,500

Response Time: <1 Nano Seconds

SSP-50XL

Rated at 120/240V Joule Rating: 1,650J Surge Amps: 45,000

Response Time: <1 Nano Seconds