





9-Year Electric

- Available in 40- and 50-gallons, First Hour Delivery up to 65 gallons
- Electronic Thermostat superior to conventional electromechanical thermostats, provides more precise temperature control and diagnostic capabilities
- Self-cleaning PEX dip tube helps reduce sediment build up and maintain efficiency
- Heavy-duty anode rod protects against corrosion
- Dry Fire Protection prevents heating element failure if energized without water in the tank
- Dual Premium 4500 Watt Stainless Steel Heating Elements
- Factory-Installed Temperature & Pressure (T&P) Relief Valve

9-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor[†] Electronic Thermostat

Profile (Short, Medium, Tall, Lowboy, etc.)	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Element Wattage (Standard)	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (Inches)	Height to top of tank (Inches)
Medium	9 40 EKRS	40	37	53	4500/4500	21	0.93	20 1/2	50
Tall	9 40 EKRT	40	36	61	4500/4500	21	0.93	20	60 1/4
Medium	9 50 EKRS	50	46	63	4500/4500	21	0.92	23	49 3/4
Tall	9 50 EKRT	50	45	65	4500/4500	21	0.90	22	60 1/2

[†]For complete information consult written warranty.

Reliance[®] Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.

©2017 Reliance Water Heater Company