



**ROCKSOLID®
NATURAL LOOK CONCRETE SEALER**

DESCRIPTION AND USES

RockSolid® Natural Look Concrete Sealer seals and protects concrete and masonry surfaces from the damaging effects of water, chemicals and UV light. This water-based film-forming formula provides a protective barrier to keep water out, protect against stains and extend the life of the concrete surface. The “natural look” low gloss finish is suitable for use on driveways, patios, walkways, pool decks, basements and more. This product is not intended for use on garage floors.

Natural Look Concrete Sealer is suitable for use on interior or exterior, stained or bare concrete and masonry surfaces. Do not use on asphalt. Natural Look Concrete Sealer is ideal for driveways, walkways, porches, patios, pool decks and more. For ongoing maintenance, surfaces previously sealed with RockSolid Natural Look Concrete Sealer may be sealed again with this product (or another water-base, film-forming sealer).

PRODUCTS

SKU	Container Size
317928	1-Gallon Natural Look Concrete Sealer

PRODUCT FEATURES

- Seals and protects surface for chemicals & stains
- Excellent water repellency
- Long-lasting formula

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Proper surface preparation is critical to achieve best results. Allow newly poured concrete to cure for a minimum of 28 days. Sweep away all loose dirt, debris and remove any vegetation that could interfere with application and performance. If necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. Remove any efflorescence with RockSolid Efflorescence Remover (sold separately). Clean the entire surface, including any oil or grease spots with RockSolid Heavy Duty Cleaner (sold separately). Scrub with a stiff bristle brush or broom. Rinse thoroughly with fresh water. A power washer is preferred. Repeat as necessary to completely clean and rinse. Allow to dry to the touch (typically 4 to 6 hours) before applying RockSolid Natural Look Concrete Sealer.

PRODUCT APPLICATION (cont.)

APPLICATION

RockSolid Natural Look Concrete Sealer is ready to use. Do not thin. Use only when air (ambient) temperature is between 50-90°F (10-32°C) and the relative humidity is below 85% during the day and night. **Do not apply in direct sunlight.** Do not apply if rain is expected within 24 hours. Use in a well ventilated area.

Mask adjacent surfaces to allow spray application up to all edges. Protect delicate foliage from overspray. Apply using a standard pump sprayer with an adjustable spray tip.* Stir container to mix product. Fill pump sprayer with product, then fully pressurize the sprayer. Set the spray tip to a medium-fine mist and spray 10-12" from the surface. Do not pour the product on the surface or allow product to puddle.

Start and stop the sprayer just off the work area to prevent drips. For larger areas, work in 6'x6' sections at a time before moving to the next section. Apply the product evenly, using a circular or oval pattern to saturate the surface. Backroll any puddles with a 3/8" to 1/2" nap roller.

For additional protection on heavy traffic areas or for more porous surfaces, wait 4 to 6 hours to recoat. Occasional touch-up or recoat may be necessary for areas subject to heavy foot or vehicle traffic.

*An alternate method is to apply with a 3/8" or 1/2" nap roller from a paint tray.

COVERAGE

Each gallon covers 200-400 square feet (single coat) depending on the porosity of the surface. Porous surfaces may require additional coats.

DRY TIME

Dry time is based on 70°F and 50% relative humidity. Allow longer dry time at lower temperatures and higher humidity. Wait a minimum of 4 to 6 hours for light foot traffic. Wait 24-48 hours before returning heavy items, furniture and vehicles. The surface will be fully cured in 72 hours.

CLEAN-UP

Wash tools and equipment with soap and water. Properly dispose of all soiled rags and unused product.



TECHNICAL DATA

ROCKSOLID® NATURAL LOOK CONCRETE SEALER

PHYSICAL PROPERTIES

Resin Type		Acrylic
Pigment		None
Solvent		Glycol Ethers, Water
Weight	Per Gallon	8.5 lbs.
	Per Liter	1.02 kg
Solids	By Weight	25.9%
	By Volume	24.2%
Volatile Organic Compounds		<100 g/l (0.83lbs./gal.)
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils (25-50µ)
Practical Coverage at Recommended DFT		200-400 sq.ft./gal. (single coat) Actual coverage will vary depending on the porosity of the surface
Dry Times @ 70-80° F (21-27°C) and 50% Relative Humidity	Touch	1 hour
	Recoat	4-6 hours
	Light Traffic	4-6 hours
	Heavy Items	24-48 hours
Shelf Life		2 years
Flash Point		200°F (93°C)
Safety Information		For additional information, see SDS



The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

NATURAL LOOK CONCRETE SEALER

GENERAL PURPOSE



Seals and Protects Surface
from Chemicals & Stains

Excellent Water Repellency

Long-Lasting Formula

LOW GLOSS CLEAR

ONE GALLON (128 FL OZ)/(3.78L)

WARNING: EYE AND SKIN IRRITANT.
See other cautions on back panel.



PAVERS



CONCRETE

RockSolid® Natural Look Concrete Sealer seals and protects concrete and masonry surfaces from the damaging effects of water, chemicals, and UV light. The water-base, film-forming formula provides a protective barrier to keep water out, protect against stains, and extend the life of your concrete. Its "natural look", low gloss finish is suitable for use on driveways, patios, walkways, pool decks, basements, and more. This product is not intended for use on garage floors.

**READ ALL INSTRUCTIONS CAREFULLY
BEFORE STARTING PROJECT**

WHERE TO USE: Use on interior or exterior, stained or bare concrete and masonry surfaces. Do not use on asphalt. Ideal for driveways, walkways, porches, patios, pool decks, and more. For ongoing maintenance, surfaces previously sealed with **RockSolid® Natural Look Concrete Sealer** may be sealed again with this product (or another water-base, film-forming sealer).

SURFACE PREPARATION: Proper surface preparation is critical to achieve best results. Allow newly poured concrete to cure for a minimum of 28 days. Sweep away all loose dirt and debris, and remove any vegetation. If necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. Remove any efflorescence with a **RockSolid® Efflorescence Remover** (sold separately). Clean entire surface, including any oil or grease spots, with **RockSolid® Heavy Duty Cleaner** (sold separately). Scrub surface with a stiff bristle brush or broom. Rinse thoroughly with fresh water, preferably with a power washer. Repeat as necessary to completely clean and rinse. Allow to dry to the touch (typically 4 to 6 hours) before applying **RockSolid® Natural Look Concrete Sealer**.

COVERAGE: Each gallon covers 200 to 400 square feet (single coat), depending on the porosity of the surface. Porous surfaces may require additional coats.

APPLICATION: **RockSolid® Natural Look Concrete Sealer** is ready to use. Do not thin. Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85% during day and night. Do not apply in direct sunlight. Do not apply if rain is expected within 24 hours. Use in well-ventilated areas.

- Mask adjacent surfaces to apply spray application up to all edges. Protect delicate foliage from overspray. Apply using a standard pump sprayer with an adjustable spray tip.*
- Stir container to mix product. Fill pump sprayer with product, then fully pressurize the sprayer. Set sprayer tip to a medium-fine mist and spray 10"-12" from the surface. Do not pour product on surface or allow product to puddle.
- Start and stop the sprayer just off the work area to prevent drips. For larger areas, work in 6' x 6' sections at a time before moving to the next section.
- Apply the product evenly, using a circular or oval pattern to saturate the surface. Backroll any puddles with a 3/8" to 1/2" nap roller.
- For additional protection on heavy traffic areas or for more porous surfaces, wait 4 to 6 hours to recoat.
- Occasional touch-up or recoat may be necessary for areas exposed to heavy foot or vehicle traffic.

*Alternate application method is to apply with a 3/8" to 1/2" nap roller from a paint tray.

DRY TIME: Wait a minimum of 4 to 6 hours for light foot traffic. Wait 24 to 48 hours before returning heavy items, furniture, and vehicles. Dry time is based on 70°F & 50% relative humidity.

CLEAN UP: Soap and water.

Learn more about shop supplies we have.