



100W



DC-AC Inverter Modified Sine Wave

Model
SAM-100-12
12 VDC - 115 VAC

Design Features

- Light weight, compact, highly portable
- Easy to install and operate
- 2.1 Amp USB Port (compatible with all new release smart phones)
- Load controlled cooling fan
- Cool surface technology
- Soft start technology
- Low battery input alarm
- Universal protection circuit – thermal, battery, overload, short circuit & earth fault
- Safety certified to UL standards



2 YEAR WARRANTY

MODEL NO. SAM-100-1 2

INPUT	BATTERY SYSTEM VOLTAGE	12 VDC
	NOMINAL INPUT VOLTAGE	13.8 VDC
	INPUT VOLTAGE RANGE	10.8 VDC to 15.4 VDC
	NO LOAD CURRENT	0.3A ± 0.1A
OUTPUT	OUTPUT VOLTAGE WAVE FORM	Modified Sine Wave
	OUTPUT VOLTAGE (FREQUENCY)	115 VAC + 10% / -2%; 60 Hz ± 5%
	OUTPUT POWER, CONTINUOUS (RESISTIVE LOAD)	100W
	OUTPUT POWER, SURGE (<1 SEC., RESISTIVE LOAD)	200W
	PEAK EFFICIENCY (AT 50% OF CONTINUOUS POWER)	90%
PROTECTIONS	USB CHARGING PORT	USB 3.0, Connector Type "A": 5 VDC, 2.1A
	LOW INPUT VOLTAGE SHUTDOWN	10.5 VDC ± 0.3 VDC. Auto reset at 11.5 VDC ± 0.3 VDC
	HIGH INPUT VOLTAGE SHUTDOWN	15.4 VDC ± 0.2 VDC. Auto reset at 15.0 VDC ± 0.2 VDC
	OVERLOAD AND GROUND FAULT SHUT DOWN	Yes. Latches in shutdown condition. Manual reset: Remove the inverter from the 12V Power Outlet. Wait for 3 min and re-insert firmly.
	OVER TEMPERATURE SHUTDOWN	Yes. Auto reset on cooling down.
	COOLING FAN	Always ON
OUTLETS	DC INPUT	12V Power Plug (Cigar Plug)
	AC OUTPUT	One NEMA5-15R Outlet
GENERAL	MONITORING: STATUS INDICATION	GREEN LED: ON - Normal; OFF - Shut Down
	OPERATING TEMPERATURE RANGE	0°C to 25°C / 32°F to 77°F at 100% loading; 26°C to 35°C / 78.8°F to 95°F at 80% loading
	OPERATING HUMIDITY	< 80%; Non-condensing
	DIMENSIONS (W X D X H)	60 x 129 x 36.5 mm / 2.36 x 5.08 x 1.44 in
SAFETY	WEIGHT	0.136 kg / 0.3 lb
	SAFETY COMPLIANCE	Conforms to UL STD 458

NOTE: Specifications are subject to change without notice