

**Remote Control
(optional)
for EVO™ Series
Inverter/Chargers**

Model
EVO-RC-PLUS



Design Features

- Program various parameters and modes of operation
- Provides real time and data logged performance details
- SD Card Slot (accepts SD Card up to 16GB) to record data
- Indicates the status of Inverter & Charging Modes
- Power ON/OFF, or switch to Standby Mode
- Includes 33 ft of RJ-45 data cable

Capture EVO™ performance data on a removable SD card. Record historic power consumption, inverter functionality, battery charging activity and many other parameters. Identifies detected faults and the conditions leading up to them. Analyze trends for more efficient use of off-grid resources.

2 YEAR LIMITED WARRANTY

		MODEL NO.	EVO-RC-PLUS
COMPATIBLE INVERTER/CHARGERS	MODEL NUMBERS	EVO-1212F EVO-1212F-HW	EVO-1224F EVO-1224F-HW
	DISPLAY	LCD DISPLAY	4 Rows, 20 Character each, Alpha-Numeric LCD Display
INPUT / OUTPUT JACKS	LED INDICATORS		Blue (Status); Red (Fault)
	RJ-45		Modular Jack, 8P8C
INPUT / OUTPUT CONNECTION	RJ-12		Modular Jack, 6P6C
	CABLE SET		RJ-45 Data Cable (Straight Wired); 10 Meters / 33 ft
ENVIRONMENT	OPERATING TEMPERATURE RANGE		-20°C to 60°C
DIMENSIONS	(W X H X D), MM		160 x 114.2 x 35.5
	(W X H X D), INCHES		6.3 x 4.5 x 1.4
WEIGHT	WEIGHT WITHOUT CABLE		0.3 kg / 0.6 lb
	WEIGHT WITH CABLES		0.4 kg / 1.0 lb

NOTE: Specifications are subject to change without notice