



6 GALLON

SUBURBAN ADVANTAGE RV WATER HEATER

Replaces Aluminum Tank Water Heaters

PORCELAIN LINED STEEL TANK

Built just like longer lasting residential tank water heaters.

ANODE ROD

Protects against tank corrosion and doubles as a drain.

OPTIONAL ELECTRIC ELEMENT


Take advantage of campsite or generator power to heat water.

INDUSTRY EXCLUSIVE FLUE TUBE Baffles

Slows combustion process to transfer more heat to water in tank.



DOOR NOT INCLUDED. SHOWN FOR ILLUSTRATION PURPOSES ONLY.

STOCK #	DESCRIPTION	
5320A	SAW6D, 6 Gallon, Direct Spark Ignition (DSI)	<i>Inside Mounted Switch for Atwood/Dometic Style Water Heaters</i> 
5321A	SAW6DE, 6 Gallon, Direct Spark Ignition (DSI) , Incoloy Electric Element	
5322A*	SAW6DEL, 6 Gallon, Direct Spark Ignition, Incoloy Electric Element, 12VDC relay included in wire box for use with gas & electric interior wall control	
6279APW	SAW6 Water Heater Door, Polar White	
6279AEB	SAW6 Water Heater Door, Black	
6279AAW	SAW6 Water Heater Door, Artic White	

*For most aluminum tank "DE" model replacements utilizing an indoor mounted switch for LP gas ignition and electric element operation, the **SAW6DEL** Advantage water heater is the direct replacement model. Please refer to the Operation Switch images on the back for additional information.

SUBURBAN ADVANTAGE PORCELAIN LINED, STEEL TANK 6 GALLON RV WATER HEATERS						
MODEL NUMBER	IGNITION	ENERGY SOURCE	BTU/h INPUT	RECOVERY GALLONS PER HOUR*		
				LP GAS	ELECTRIC ELEMENT	GAS/ELECTRIC COMBINED
SAW6D [^]	DIRECT SPARK	LP GAS	10,000	8.48		
SAW6DE [^]	DIRECT SPARK	LP GAS & 1440 WATT ELECTRIC ELEMENT, 120 VAC		8.48	6.10	14.58
SAW6DEL ^{^^}	DIRECT SPARK	LP GAS & 1440 WATT ELECTRIC ELEMENT, 120 VAC		8.48	6.10	14.58

[^] Requires Switch 234589 (Inside mounted switch for control of water heater gas ignition)

^{^^} Requires Switch 232882 (12 Volt ON/OFF Switch mounted inside for control of water gas ignition and powers the electric element circuit)

*Recovery rate calculations based on temperature rise of 100° F (input water temperature of 30° F). Varies based on LP supply. Please refer to the recovery chart on back for additional information.

INSTALLATION AND SERVICE MUST BE PERFORMED BY A QUALIFIED INSTALLER, SERVICE AGENCY OR THE GAS SUPPLIER

THE SUBURBAN ADVANTAGES:


- Replaces aluminum tank RV water heaters
- Longer lasting, residential style porcelain lined steel tank
- Repositionable module board provides installation flexibility
- Backed by a 2 year limited warranty and the tank is backed by a 3 year tank limited warranty - the best in the RV industry
- Assembled in the USA by Suburban, the leader in RV water heaters.

Suburban Advantage Water Heater doors are available. Sold Separately.

Operate Gas and/or Electric Ignition from inside the RV!

DEL models provide the additional convenience of powering the electric element from the interior using a single switch. Direct Spark Ignition (D, DE) models operate with an indoor mounted switch to control water heater gas ignition. Please see dealer/retailer for the model best suited for your replacement.

Sold Separately.



DEL MODEL 12 VOLT ON/OFF SWITCH

White: #232882
Black: #233111
Cream: #232881



D, DE MODEL ON/OFF SWITCH

White: #234589
Black: #234229
Cream: #234795



Domatic/Atwood Style Direct Spark Ignition with Electric Element Indoor Mounted Switch.

RECOVERY RATE CHART

INPUT WATER TEMPERATURE	SUBURBAN RECOVERY RATE USING LP GAS (Gallons Per Hour)	ELECTRIC ELEMENT RECOVERY RATE (Gallons Per Hour)	COMBINED LP GAS & ELECTRIC ELEMENT RECOVERY RATE (Gallons Per Hour)
30° F	8.48	6.10	14.58
50° F	10.61	6.10	16.71
70° F	14.14	6.10	20.24

Recovery Rate as defined in Clause 3, Definitions in ANSI Z21.10.1-2017 ·CSA 4.1-2017

UNIT DIMENSIONS: 12.50" H x 16.125" W x 17.625" D | **CUTOUT DIMENSIONS:** 12.625" H x 16.25" W
Specifications are subject to change without notice.



A Division of AIRXCEL

Shop for quality Suburban products on our website.

Learn more about RV water heaters we have.