

## PRODUCT SAFETY DATA SHEET

Document number.: PSDS\_CR CC15.01

The batteries are exempt articles and are not subject to the OSHA Hazard Communication Standard Requirement. This sheet is only provided as technical information and is referred normal use of the product in question. Chao Chuang makes no warranty expressed or implied.

### Section 1-Product and Company Identification

● Product Name Coin type Lithium Manganese Dioxide Batteries(CR)	Sizes All	Date of preparation Jan. 9, 2015
● Company: JINTAN CHAOCHUANG BATTERY CO.,LTD.		

### Section 2-Composition/Information on Ingredients

Ingredient	CAS#	Content(wt%)
Manganese Dioxide	1313-13-9	15 to 40
Propylene Carbonate	108-32-7	2 to 6
1,2-Dimethoxyethane	110-71-4	1 to 5
Lithium Perchlorate	7791-03-9	0 to 1.5
Lithium or Lithium Alloy	7439-93-2	1 to 5
Graphite	7782-42-5	1 to 4

\*) Lithium content for each cell

Model	Li content(g)	Model	Li content(g)
CR2012	0.014	CR2032	0.065
CR2016	0.023	CR2430	0.090
CR2025	0.048	CR2450	0.162
CR1632	0.038	CR1620	0.023

### Section 3–Hazards Identification

This contains lithium, organic solvent, and other combustible materials. For this reason, improper handling of the battery could lead to distortion, leakage\*, overheating, explosion, or fire and cause human injury or equipment trouble. Please strictly observe safety instructions. (\*leakage is defined as an unintended escape of liquid from a battery.)

### Section 4–First Aid Measures

None unless internal materials exposure. If contents are leaked out, observe following instructions

- |            |   |
|------------|---|
| Inhalation | Fumes can cause respiratory irritation. Remove to fresh air and consult a physician.  |
| Skin       | Immediately flush skin with plenty of water. If itch or irritation by chemical burn persists, consult a physician.                                      |
| Eyes       | Immediately flush eye with plenty of water for at least 15 minutes. Consult a physician immediately   |
| Ingestion  | If swallowing a battery, consult a physician immediately.<br>If contents come into mouth, immediately rinse by plenty of water and consult a physician. |

### Section 5–Fire Fighting Measures

- |                         |  |
|-------------------------|--|
| Extinguishing Media     | Extinguisher of alkaline metal fire is effective.<br>Plenty of cold water is also effective to cool the surrounding area and control the spread fire. But hydrogen gas may be evolved by the reaction of water and lithium and it can form an explosive mixture. Therefore in the case that lots of lithium batteries are burning in a confined space, use a smothering agent. |
| Fire fighting procedure | Use self-contained breathing apparatus and full protective gear not to inhale harmful gas.   |

### Section 6–Accidental Release Measures

NA

Section 7-Handling and Storage

1) Handling

Never swallow. Never charge. Never hear. Never expose to open flame. Never disassemble. Never reverse the positive and negative terminals when mounting. Never short-circuit the battery. Never weld the terminal or wire to the body of the battery directly. Never use different batteries together. Never touch the liquid leaked out of battery. Never bring fire close to battery liquid. Never keep in touch with battery.

2) Storage

Never let the battery contact with water. Never store the battery in hot and high humid place

Section 8-Exposure Controls, Personal Protection

Respiratory Protection		NA
Ventilation	Local Exhaust	NA
	Mechanical	NA
	Special	NA
	Other	NA
Eye Protection		NA
Protective Glove		NA
Other protective clothing		NA

Section 9-Physical/Chemical Characteristics

NA

Section 10-Stability and Reactivity

Stability	Stable
Incompatibility	Water
Hazardous polymerization	Will not occur
Condition to avoid	See section 7.
Hazardous Decomposition or Byproducts	Hydrogen

Section 11-Toxicological Information

NA

Section 12-Ecological Information

NA

