





## Elbows, Sweeps and Accessories

### Schedule 80 Elbows — Special Radius (continued)

SEGMENT	PLAIN END CAT. NO.	BELLED END CAT. NO.	NOM. DIAM. (IN.)	RADIUS (IN.)	PLAIN END STD. CTN.	BELLED END STD. CTN.
45° ELBOW 	UB7CF	—	1	18	1	—
	UB7DF	—	1	24	1	—
	UB7FF	—	1	36	1	—
	UB7HF	—	1	48	1	—
	UB7DG	—	1¼	24	1	—
	UB7FG	—	1¼	36	1	—
	UB7HG	—	1¼	48	1	—
	UB7CH	—	1½	18	1	—
	UB7DH	UB7DHB	1½	24	1	1
	UB7FH	—	1½	36	1	—
	UB7HH	—	1½	48	1	—
	UB7CJ	—	2	18	1	—
	UB7DJ	UB7DJB	2	24	1	1
	UB7FJ	UB7FJB	2	36	1	1
	UB7HJ	—	2	48	1	—
	UB7DK	UB7DKB	2½	24	1	1
	UB7FK	—	2½	36	1	—
	UB7HK	—	2½	48	1	—
	UB7CL	—	3	18	1	—
	UB7DL	UB7DLB	3	24	1	1
	UB7FL	UB7FLB	3	36	1	1
	UB7HL	—	3	48	1	—
	UB7DN	UB7DNB	4	24	1	1
	UB7FN	UB7FNB	4	36	1	1
UB7HN	—	4	48	1	—	
UB7FP	—	5	36	1	—	
UB7HP	—	5	48	1	—	
UB7FR	—	6	36	1	—	
UB7HR	—	6	48	1	—	
UB7IR	—	6	60	1	—	
30° ELBOW 	UB6FN	—	4	36	1	—
	UB6FR	—	6	36	1	—
22½° ELBOW 	—	UB5DHB	1½	24	—	20
	—	UB5DJB	2	24	—	20
	—	UB5FJB	2	36	—	25
	—	UB5DKB	2½	24	—	15
	UB5DL	UB5DLB	3	24	1	10
	—	UB5FLB	3	36	—	1
	UB5DN	UB5DNB	4	24	1	5
	—	UB5FNB	4	36	—	1
UB5FP	—	5	36	1	—	
11¼° ELBOW 	UB3FP	—	5	36	1	—

Note: Elbows 72" and larger may be shipped in segments. Consult factory for specifics.

### Flexible PVC Elbows



- UL Listed for exposed and direct-burial applications in accordance with Article 356 of the NEC®
- 0°–90° bending and offset applications
- O-ring seal for moisture-tight connections
- Maintains round shape throughout bend
- Sunlight resistant
- Non-corrosive — all PVC and Neoprene material
- Fully assembled and ready to use

CAT. NO.	SIZE (IN.)	STD. CTN.	STD. WT. (LBS.)	LENGTH FULLY ASSEMBLED (IN.)
UAFAD	½	8	1.6	8.5
UFAFE	¾	6	1.9	9.6
UFAFF	1	6	2.4	11.9

NEC and National Electrical Code are registered trademarks of the National Fire Protection Association, Inc.