

## WINEGARD® MODEL RP-4200 THICK ROOF KIT

The RP-4200 is designed for use with the RD-4600 or RD-4610 Crank-up Digital Satellite Systems (with molded interior control parts) where roof thickness of RV is 5 to 6-3/4 inches. The RP-4200 includes one directional handle extension and elevating shaft worm gear assembly.

Refer to the table below for the correct directional handle and elevating shaft measurements. Remember to glue extensions (PVC glue is recommended) and handle together after checking that you have the correct length. For snug fit, it is important to install shim(s) supplied with RD-4600 crank-up antenna between extension and gear housing. Do not glue this connection. Refer to page 4, Step 9/NOTE in the RD-4600 instruction manual.

ROOF THICKNESS	DIRECTIONAL HANDLE	Elevating Shaft			W/RW-1000
		Handle	Extension 1	Extension 2	
6 3/4"	7 1/2"	No Change	No Change	2"	8 3/4"
6 1/2"	7 1/4"	No Change	No Change	1 3/4"	8 1/2"
6 1/4"	7"	No Change	No Change	1 1/2"	8 1/4"
6"	6 3/4"	No Change	2"	1 1/2"	8"
5 3/4"	6 1/2"	No Change	1 3/4"	1 1/2"	7 3/4"
5 1/2"	6 1/4"	1 3/4"	No Change	No Change	7"
5 1/4"	6"	1 3/4"	No Change	2"	6 3/4"
5"	5 3/4"	1 3/4"	No Change	1 1/4"	6 1/2"